

DCR403 - 3901/022, Table 1(a) - Type Variants		
Variant No.	Finished Wire Or Cable Characteristics	
	Max Φ (mm)	Max Weight (kg/km)
01	1.19	3.41
02	1.31	4.40
03	1.43	5.51
04	1.61	7.33
05	1.85	10.51
06	2.14	15.47
07	1.80	5.76
08	2.03	7.68
09	2.27	9.55
10	2.58	13.01
11	3.07	18.84
12	3.69	30.37
13	1.89	7.48
14	2.15	10.10
15	2.40	12.90
16	2.74	17.73
17	3.30	27.81
18	3.93	39.76
19	2.14	12.99
20	2.43	17.11
21	2.71	21.11
22	3.08	28.35
23	3.66	38.83
24	4.36	55.42
25	2.52	20.49
26	2.89	26.98
27	3.33	40.13
28	4.39	42.30
29	5.15	58.72
30	6.02	95.10
31	4.69	58.99
32	5.50	81.78
33	6.44	121.47
34	5.20	80.79
35	6.11	111.08
36	7.15	163.72
37 to 72	no changes	

	indicates changed value
--	-------------------------

DCR403 - 3901/022, Para. 4.8.8 Cut-through Resistance									
Wire Size (mm ²)	0.08	0.15	0.21	0.34	0.60	0.93	1.20	2.00	3.00
Cut-through Load (kg)	1.5	2	2.5	3.5	4.5	5.5	6.5	7	7.5

DCR403 - 3901/022, Para. 4.8.13 Abrasion Resistance									
Wire Size (mm ²)	0.08	0.15	0.21	0.34	0.60	0.93	1.20	2.00	3.00
Scrape Abrasion (kg)	0.2	0.3	0.3	0.4	0.4	0.5	0.6	0.9	0.9