

TABLE 1(a) – TYPE VARIANTS

CONTACT SIZE	SHELL SIZE (2)	MAX. WEIGHT (g) (1)				MATING FORCE (N. max)	UNMATING FORCE	
		VARIANT 01		VARIANT 02			N. min	N. max
		Male	Female	Male	Female			
#26	A	1.05	1.0	1.35	1.45	11.90	0.95	11.90
	B	1.35	1.25	1.75	1.80	18.70	1.50	18.70
	C	1.60	1.45	2.15	2.20	22.10	1.80	22.10
	D	1.80	1.65	2.35	2.40	28.90	2.35	28.90
	E	2.10	1.88	2.70	2.69	35.70	2.90	35.70
	F	2.35	2.10	2.95	2.90	42.50	3.50	42.50
	G	2.50	2.20	3.15	3.05	56.10	4.60	56.10
	H	3.44	2.95	4.20	4.10	86.70	7.10	86.70
	J	6.10	4.75	7.30	6.45	178.80	14.50	178.80

NOTES

- Without contacts but see Para. 4.5.4.9. See ESCC Detail specification No. 3401/083 for contact weights.
- See Figure 2.

TABLE 1(b) – MAXIMUM RATINGS

No.	CHARACTERISTICS	SYMBOL	MAXIMUM RATING		UNIT
			MIN.	MAX.	
1	Working Voltage (Sea Level) -Gauge 26 Contacts Variant 01 and Contacts Variant 02	U _R		150	V _{ms}
2	Operating Temperature Range	T _{op}	-55	+125	°C
3	Storage Temperature Range	T _{stg}	-65	+125	°C