



DOCUMENT CHANGE REQUEST

DCR number 927 Changes required for: General

Date: 2015/11/25

Date sent: 2015/04/13

Status: IMPLEMENTED

Originator: Steve Thacker

Organisation: ESCC Executive Secretariat

Title: Capacitors, Fixed, Chips, Ceramic Dielectric, Type I with Flexible Terminations, Based on Types

Number: 3009/040

Issue: 1

Other documents affected:

Page:

Total reformat/re-write of ESCC Detail Specification 3009/040 issue 1 as part of the ongoing conversion of legacy ESA/SCC specifications to the ESCC format as well as reflecting changes resulting from the conversion of ESCC Generic Specification No. 3009 issue 1 (per DCR695).

The layout, format and general content of 3009/040 issue 2 is based on other converted ESCC Detail Specifications (see attached for proposed 3009/040 issue 2 Draft E).

The technical content of ESCC 3009/040 issue 2 remains closely based on the original ESCC 3009/040 issue 1 except as detailed herein.

Paragraph:

See below

Original wording:

As per original Specification

Proposed wording:

Total reformat of this Detail Specification (from the range of various ESCC Detail Specifications, 3009/xxx, for capacitors under Generic Specification No. 3009) as part of the ongoing conversion to the ESCC format.

See below for summary of changes, also see attached the proposed 3009/040 Issue 2 Draft E.

Note: known support for active procurement against this specification includes the following Manufacturers:

- Eurofarad/France (is willing to support procurement of all Variants).

Summary of changes to the current format, layout and content is as follows:

1) General

Rewording and restructure of various sections and paragraphs of the specification, plus other editorial changes based on the layout and editorial content of other Detail Specifications already converted to ESCC format.

In addition, editorial and technical amendments resulting from the changes made to the test requirements of the Generic



DOCUMENT CHANGE REQUEST

DCR number 927 Changes required for: General

Date: 2015/11/25

Date sent: 2015/04/13

Status: IMPLEMENTED

Originator: Steve Thacker

Organisation: ESCC Executive Secretariat

Specification No. 3009.

Specific amendments include:

- Table 3: Delete Insulation Resistance, and Temperature Characteristic for each capacitance value (due to SCC level B being deleted)
- Para. 4.7.1 & Table 4 is deleted (due to SCC level B being deleted)
- Table 6 only includes specified electrical measurement requirements as required for the various Chart F4 Qual level tests (editorial change)
- Table 6: Adhesion is renamed as Robustness of Terminations
- Table 6: Add note that the capacitance values recorded during Mounting may be used as initial measurements for other tests (to provide the same flexibility included in 3009 issue 1)
- Table 6: Climatic Test Sequence requirements are deleted.
- Table 6: Damp Heat Steady State is deleted and replaced by Steady State Humidity (85/85) test requirements.
- Table 6: Add notes applicable to Operating Life, to explain when the 1000h & 2000h measurements apply.

2) Table 1(a) (& Notes 2, 3 & Para 4.2, Table 3):

For variants 01 to 06, the finish definition is simplified to be: Sn/Pb plating (was 'coating')

Add new note and associated new deviation to the Generic Specification for Variants 07 to 12: "Variants 07 to 12 are not suitable for solder assembly methods. They shall be assembled using glue or wire bond techniques."; "Solderability: not applicable to Variants 07 to 12."

3) Table 1(a) Note 1, Table 1(b) & Para 4.5.2.3:

The range of components is expanded to also include components with rated voltage = 200V (see attached for details)

A note is added to the available range of capacitance values: "Any capacitance value in the capacitance range may be available on request."

4) Figure 2: Dimension 'e' max limits are changed (see attached for details)(to be consistent across the range of currently published 3009/xxx specs)

5) Para 4.5.1: The 2nd sentence is amended to read: "The information to be marked on the component or its primary package shall be:" (in order to cater for small components and to be consistent with all other 3009/xxx Detail specs)

6) Table 2 & Table 6: Units for Insulation Resistance are rewritten as Gohm.nF (instead of 'Mohm.uF')

7) Table 2 Tangent of Loss Angle: The inequality symbol in the last line is corrected to be ' ' i.e. 'Cn 50pF' (was 'Cn > 50pF')

8) Table 5 (Para 2.5 in issue 4)

Delete test conditions that are already specified in the Generic spec (Temperature & Voltage).

Justification:

