



DOCUMENT CHANGE REQUEST

DCR number 1182 Changes required for: General

Date: 2019/02/08

Date sent: 2018/09/28

Originator: Celine Dumortier

Organisation: Radiall

Status: IMPLEMENTED

Title: RF Coaxial Connectors Type SMA 50 Ohms (Female Contact)

Number: 3402/002

Issue: 6

Other documents affected:

Page:

26

Paragraph:

FIGURE 2(b) – VARIANTS

Original wording:

VARIANT 03 - STRAIGHT PLUG WITH CABLE CLAMP, SOLDER TYPE, FOR SEMI-RIGID CABLE Ø6.35mm (0.25)

Proposed wording:

VARIANT 03 - STRAIGHT JACK WITH CABLE CLAMP, SOLDER TYPE, FOR SEMI-RIGID CABLE Ø6.35mm (0.25)

Justification:

The drawing and the title correspond to the SMA male connectors instead of female for ESCC3402002 (replace the drawing with this in attached)



DOCUMENT CHANGE REQUEST

DCR number 1182 Changes required for: General

Date: 2019/02/08

Date sent: 2018/09/28

Originator: Celine Dumortier

Organisation: Radiall

Status: IMPLEMENTED

Title: RF Coaxial Connectors Type SMA 50 Ohms (Female Contact)

Number: 3402/002

Issue:

6

Other documents affected:

Page:

27

Paragraph:

FIGURE 2(b) – VARIANTS

Original wording:

VARIANT 04 - STRAIGHT PLUG WITH CABLE CLAMP, SOLDER TYPE, FOR SEMI-RIGID MICROPOROUS CABLE Ø6.35mm (0.25")

Proposed wording:

VARIANT 04 - STRAIGHT JACK WITH CABLE CLAMP, SOLDER TYPE, FOR SEMI-RIGID MICROPOROUS CABLE Ø6.35mm (0.25")

Justification:

The drawing and the title correspond to the SMA male connectors instead of female for ESCC3402002.



DOCUMENT CHANGE REQUEST

DCR number 1182

Changes required for: General

Originator: Celine Dumortier

Date: 2019/02/08

Date sent: 2018/09/28

Organisation: Radiall

Status: IMPLEMENTED

Title: RF Coaxial Connectors Type SMA 50 Ohms (Female Contact)

Number: 3402/002

Issue: 6

Other documents affected:

Page:

38

Paragraph:

FIGURE 2(b) – VARIANTS

Original wording:

Maximum weight 2.7g

Proposed wording:

Maximum weight 3.3g

Justification:

VARIANT 15 - SQUARE FLANGE RECEPTACLE, FRONT MOUNTING

The maximum weight is of 2,7g instead of 3,3g, for the maximum length of A and B.



DOCUMENT CHANGE REQUEST

DCR number 1182 Changes required for: General

Date: 2019/02/08

Date sent: 2018/09/28

Originator: Celine Dumortier

Organisation: Radiall

Status: IMPLEMENTED

Title: RF Coaxial Connectors Type SMA 50 Ohms (Female Contact)

Number: 3402/002

Issue:

6

Other documents affected:

Page:

92

Paragraph:

FIGURE 2(b) – VARIANTS

Original wording:

Maximum voltage standing wave ratio (VSWR) $1.1 + 0.01 f$ (GHz)

Proposed wording:

Maximum voltage standing wave ratio (VSWR) $1.1 + 0.001 f$ (GHz)

Justification:

VARIANT 72 – SQUARE FLANGE RECEPTACLE TAB CONTACT, LOW RF LEAKAGE

In the table ELECTRICAL CHARACTERISTICS, the Maximum voltage standing wave ratio (VSWR) is $1.1 + 0.001 f$ (GHz) instead of $1.1 + 0.01 f$ (GHz). This is due to a typing error of Radiall during the request of variant creation (DCR 408). The Radiall connector issue of this request is R125612140X, please find attached the LAT test report 2005.45.2203 corresponding.



DOCUMENT CHANGE REQUEST

DCR number 1182 Changes required for: General

Date: 2019/02/08

Date sent: 2018/09/28

Originator: Celine Dumortier

Organisation: Radiall

Status: IMPLEMENTED

Title: RF Coaxial Connectors Type SMA 50 Ohms (Female Contact)

Number: 3402/002

Issue:

6

Other documents affected:

Page:

91

Paragraph:

FIGURE 2(b) – VARIANTS

Original wording:

Operating temperature range -65 to +165°C

Proposed wording:

Operating temperature range -65 to +105°C

Justification:

VARIANT 71 – ELBOW RECEPTACLE, SQUARE FLANGE (SOLID CONTACT)

Operating temperature range is of -65 to +165°C instead of -65 to +105°C.

The mistake is appeared between the issue 3 to 4 (DCR 826).

Attachments:

esatds_r126.410.041.docx, demande_ajout_variante_esc3402_00249.pdf, drawing_variante_4.docx, esatds_r126.410.061.docx, esatds_r126.410.031.docx, drawing_variante_3.docx, lat_test_report_n°2005_45_2203__r125612140x.pdf, esatds_r126.410.051.docx

Modifications:

N/A

Approval signature:

Date signed:

2019-02-08

