



DOCUMENT CHANGE REQUEST

DCR number	1661	Changes required for:	General	Originator:	Steve Jeffery
Date:	2024/05/21	Date sent:	2024/04/19	Organisation:	ESCC Executive
Status:	IMPLEMENTED				

Title: Capacitor Filters C-Type Feedthrough Electromagnetic Interference Suppression Hermetically

Number: 3008/020 Issue: 4

Other documents affected:

Page:

7, 12, 15

Paragraph:

1.5, 2.6.2, Appendix A

Original wording:

- Para. 1.5, Note 1: ... For Variants with UR = 100V at Tamb +85°C, derate linearly to 75V at Tamb = +125°C. For Variants with UR = 200V at Tamb +85°C, derate linearly to 150V at Tamb = +125°C.

- Para. 2.6.2, Test Temperature tolerance is (+0 -5) / (+5 -0) °C.

Proposed wording:

The proposed changes to ESCC Detail Spec 3008/020 are as a result of recent discussion between the mfr Exxelia and the ESCC T.W.

See the attached mark-up escc3008020iss5 DraftA for DCR review.docx (proposed changes are highlighted in yellow).

(Note similar additional changes, detailed in the Comments to DCRs 1625 thru 1632, which were originally raised in order to convert the 8 other 3008/### specs to the ESCC format.)

Justification:

- The revision of the Voltage derating, as advised by Exxelia, is considered by the ESCC T.W. to be acceptable.
- Harmonisation across all 3006/### Detail Specs and 3008/### Detail Specs of the tolerance margin for the high and low test temperatures defined in High and Low Temperatures Electrical Measurements, Burn-in and Operating Life.
- For the added Deviation in Appendix A, the ESCC T.W. considers it acceptable for Exxelia to perform the Room Temperature Insertion Loss measurements during Screening (Chart F3) on a sample basis instead of 100%.

Attachments:

esc3008020iss5_drafta_for_dcr_review.docx

Modifications:

N/A

Approval signature:

A handwritten signature in black ink, appearing to be a stylized name or set of initials.

Date signed:

2024-05-21