	ES(<u>;C</u>	[C	DCUMENT	CHANGE REQUEST	
DCR number	549	Changes re-	quired for: G	ene	eral	Originator: Steve Thacker - ESCC	
Date: 2009/10)/07	Date sent: 2	2009/10/07			Organisation:	
Status: IMPLE	EMENTED						
Title:	Resistor Fixed Su	Irface Mount Th	nin Film Non H	ler	metically Sealed	,	
Number:	4001/029		Issue:		1		
Other documen	ts affected:						
Page:							
The layout and content of this Specification totally rewritten. See also details below.							
Paragraph:							
The layout and below.	content of this Spe	ecification totally	v rewritten. Se	e a	also details		
Original wording	g:						
Proposed wordi	ng:						
The following a conversion of s ESCC4001.	mendments and a pecifications to the	dditions detail th ESCC format a	e Total reforr as well as mal	nat king	of this Detail Spo g it consistent wit	ecification as part of the ongoing h the current issue of Generic spec	
See below for s	summary of all cha	nges; also see a	attached prop	ose	ed 4001/029 Issu	e 2 Draft A.	
Note: The layou ESCC Detail Sp	ut, format and gene pecifications (e.g. 4	eral content of 4 4001/026).	001/029 issue	ə 2	is based closely	on other re-written/converted, published	
Note: known su Vishay-Selb Dra	Note: known support for active procurement against this specification includes the following Manufacturer: Vishay-Selb Draloric/Germany (is willing to support procurement of all variants).						
Summary of ch	anges to the curre	nt format, layou	t and content	is a	as follows:		
1. Rewording, r editorial change format.	estructure, modific es based on the us	ation and removulation and removulation and removal and removal the second second second second second second s	val of various editorial conte	seo nt o	ctions and paragi of other Detail Sp	aphs of the specification, plus other ecifications already converted to ESCC	
2. In the Maxim ESCC4001 & E	um Ratings table a SCC2134000)(in r	amend "Insulatio new Para 1.5).	on Voltage" to	be	e "Isolation Voltag	e" with symbol Ui (to be consistent with	

E	SC	C	DOCUMENT	CHANGE REQUEST
DCR number	549	Changes required for:	General	Originator: Steve Thacker - ESCC
Date: 2009/10/07		Date sent: 2009/10/07		Organisation:
Status: IMPLEMENT	ED			
3. Figure 1 is deleted a new Para 1.5).	& the Parame	er Derating Requiremer	its moved to become r	ote 1 to the Maximum Ratings table (in
4. Figure 3 is amende	d to refer to R	n (in new Para 1.7)		
 5. Paras 4.2.1, 4.2.2, 4 including: Para 4.2.2(b) Third H The deviations from Delete the deviation Delete the Overload 4001) 	4.2.3, 4.2.4 an Iarmonic Cont Para 4.2.3(a), 4.2.3(d) , whic deviation from	e amended to make the rol or Current Noise is re (b) & (c) are replaced by th is replaced by note 1 i n Para 4.2.4(a) (as Overl	existing deviations cor enamed as Non-Linear y single new Para 2.1. n Para 2.5.1. oad is no longer requir	nsistent with the contents of ESCC4001 ity 1.1(c). red for Qualification testing in ESCC
6. New Para 2.4 for Re	esistance to S	oldering Heat test is add	led (to be consistent w	ith ESCC 4001).
7. Para 4.7, 4.7.1, 4.7. 2.1.1.1(c))	2, 4.7.3, âOv	verloadâ. (=Burn-in) requ	uirements are deleted	effectively replaced by new Para
8. Table 2, Insulation I 2.6 (in new Para 2.5.1	Resistance tes).	st is added with note 3 st	ating guaranteed but r	not tested, to be consistent with new Para
9. Para 4.6.2 & Table single sample of 5 cor	 High & Low nponents from 	Temp Electrical Measure the total production lot	rements: For test TCR (to be consistent with I	the sampling is amended to be a simple ESCC 4001)(in new Para 2.5.2).
10. Table 4 is deleted	(to be consist	ent ESCC 4001) (effectiv	vely replaced by new F	Para 2.1.1.1(c))
11. Table 5(a) is delet	ed (effectively	replaced by new Para 2	.1.1.1(c))	
12. Table 5(b), "contin	uous" is adde	d to the Test Voltage co	ndition for clarification	purposes.
13. Table 6 is amende Delete drying "Proced	d to be consis ure I" referenc	stent with 4001; Only tes e from both Solderability	ts that include electrica / & Resistance to Sold	al measurement are included in Para 2.6. ering Heat.
Justification:				
(See also change deta	ails for each ite	em above)		
Part of the ongoing ac the format and presen	tivity of conve tation to be co	rsion of ESA/SCC layou posistent with the various	t specifications to the I s other ESCC Detail Sp	ESCC format. Amendments are made to becifications, already converted to

ESCC format, as well as the latest ESCC Generic Specification No. 4001 issue 2.

Attachments:

4001029issue2B.pdf, null

Modifications:

Changes and corrections to the original DCR wording, based on the review comments provided by Manufacturer, are as follows:

The proposed, attached specification shall be 4001/029 issue 2 Draft B.

For item 5: add reference to Para 4.2.5 and add the following bullet:

" - Delete the deviations from Paras 4.2.4(c) & 4.2.5(b) (as there is no deviation applicable)."

Delete item 12 (as the operating life is not 'continuous' but is the standard ON/OFF method per ESCC4001 para 8.13).

Approval signature:

flain-7 2)(_

Date signed:

2009-10-07



Pages 1 to 12

RESISTOR, FIXED, SURFACE MOUNT, THIN FILM, NON-

HERMETICALLY SEALED

BASED ON TYPE TNPS

ESCC Detail Specification No. 4001/029

Issue 2 Draft B	June 2010



Document Custodian: European Space Agency - see https://escies.org



LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2010. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.



PAGE 3 ISSUE 2 Draft B

DOCUMENTATION CHANGE NOTICE

(Refer to https://escies.org for ESCC DCR content)

DCR No.	CHANGE DESCRIPTION
549	Specification updated to incorporate editorial and technical changes per DCR.



ISSUE 2 Draft B

TABLE OF CONTENTS

<u>1.</u>	GENERAL	<u>5</u>
1.1	Scope	5
1.2	Applicable Documents	5
1.3	Terms, Definitions, Abbreviations, Symbols and Units	5
1.4	The ESCC Component Number and Component Type Variants	5
1.4.1	The ESCC Component Number	5
1.4.1.1	Characteristics and/or Ratings Codes	5
1.4.2	Component Type Variants and Range of Components	6
1.5	Maximum Ratings	6
1.6	Physical Dimensions	7
1.7	Functional Diagram	7
1.8	Materials and Finishes	8
1.8.1	Case	8
1.8.2	Terminations	8
<u>2.</u>	<u>REQUIREMENTS</u>	<u>8</u>
2.1	General	8
2.1.1	Deviations from the Generic Specification	8
2.1.1.1	Deviations from Screening Tests (Chart F3)	8
2.1.1.2	Deviations from Qualification and Periodic Tests (Chart F4)	8
2.2	Marking	9
2.3	Robustness of Terminations - Substrate Bending Test	9
2.4	Resistance to Soldering Heat	9
2.5	Electrical Measurements at Room, High and Low Temperatures	9
2.5.1	Room Temperature Electrical Measurements	9
2.5.2	High and Low Temperatures Electrical Measurements	10
	Fight and Low Temperatures Electrical measurements	
2.6	Intermediate and End-Point Electrical Measurements	11
2.6 2.7	Intermediate and End-Point Electrical Measurements Operating Life Conditions	



1. <u>GENERAL</u>

1.1 <u>SCOPE</u>

This specification details the ratings, physical and electrical characteristics and test and inspection data for the component type variants and/or the range of components specified below. It supplements the requirements of, and shall be read in conjunction with, the ESCC Generic Specification listed under Applicable Documents.

1.2 <u>APPLICABLE DOCUMENTS</u>

The following documents form part of this specification and shall be read in conjunction with it:

(a) ESCC Generic Specification No. 4001.

1.3 <u>TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS</u> For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 shall apply.

1.4 THE ESCC COMPONENT NUMBER AND COMPONENT TYPE VARIANTS

1.4.1 The ESCC Component Number The ESCC Component Number shall be constituted as follows:

Example: 4001029012490F3

- Detail Specification Reference: 4001029
- Component Type Variant Number: 01 (as required)
- Characteristic code: Resistance Value (249Ω): 2490 (as required)
- Characteristic code: Resistance Tolerance (±1%): F (as required)
- Characteristic code: Temperature Coefficient (±50 x 10 ⁻⁶/^oC): 3 (as required)

1.4.1.1 Characteristics and/or Ratings Codes

Characteristics and/or ratings to be codified as part of the ESCC Component Number shall be as follows:

(a) Resistance Value expressed by means of the following codes in accordance with ESCC Basic Specification No. 21700. The unit quantity shall be ohm (Ω):

Resistance Value (Ω)	Code
XX.X	XXRX
XXX	XXX0
XXX 10 ¹	XXX1
XXX 10 ²	XXX2
XXX 10 ³	XXX3
XXX 10 ⁴	XXX4



ISSUE 2 Draft B

PAGE 6

(b) Resistance Tolerance expressed by the following code letters in accordance with ESCC Basic Specification No. 21700:

Tolerance (± %)	Code Letter
0.1	В
0.5	D
1	F

(c) Temperature Coefficient

Temperature Coefficient expressed by the following codes:

Temperature Coefficient (± 10 ⁻⁶ /°C)	Code
15	1
25	2
50	3

1.4.2Component Type Variants and Range of ComponentsThe component type variants and range of components applicable to this specification are as follows:

Variant	Style	Resistance	e Range R _n	Tolerance	Value	Temperature	Critical	Weight
Number	(Note 1)	Min (Ω)	Max (MΩ)	(± %)	Series	(±10 ⁻⁶ /°C)	Resistance (kΩ)	(g)
01	0603	10	0.221	0.1, 0.5, 1	E96	15, 25, 50	56.25	0.002
02	0805	10	0.422	0.1, 0.5, 1	E96	15, 25, 50	180	0.006
03	1206	10	1	0.1, 0.5, 1	E96	15, 25, 50	160	0.008

NOTES:

1. See Physical Dimensions.

1.5 MAXIMUM RATINGS

The maximum ratings shall not be exceeded at any time during use or storage.

Maximum ratings shall only be exceeded during testing to the extent specified in this specification and when stipulated in Test Methods and Procedures of the ESCC Generic Specification.

Characteristics	Variant Number	Style	Symbols	Limits	Units	Remarks
Rated Dissipation	01 02 03	0603 0805 1206	P _n	100 125 250	mW	Note 1



ISSUE 2 Draft B

Characteristics	Variant Number	Style	Symbols	Limits	Units	Remarks
Limiting Element Voltage	01 02 03	0603 0805 1206	UL	75 150 200	V	-
Rated Voltage	All	All	U _R	$\sqrt{(P_n \times R_n)}$	V	Note 2
Isolation Voltage	01 02 03	0603 0805 1206	Ui	100 200 300	Vrms	-
Operating Temperature Range	All	All	T _{op}	-55 to +125	°C	T _{amb}
Storage Temperature Range	All	All	T _{stg}	-55 to +125	°C	-
Soldering Temperature	All	All	T _{sol}	+260	°C	Note 3

NOTES:

At $T_{amb} \le +70^{\circ}$ C. For $T_{amb} > +70^{\circ}$ C derate linearly to 0W at $T_{amb}=+125^{\circ}$ C. Shall never exceed Limiting Element Voltage. $R_n =$ rated resistance. 1.

2.

Duration 10 seconds maximum. 3.

PHYSICAL DIMENSIONS 1.6



Variant	Style	Dimensions (mm)										
Number		L	_	W		ŀ	1	T1, T2				
		Min	Max	Min	Max	Min	Max	Min	Max			
01	0603	1.5	1.7	0.75	0.95	0.35	0.55	0.1	0.5			
02	0805	1.85	2.15	1.1	1.4	0.35	0.55	0.2	0.6			
03	1206	3.05	3.35	1.45	1.75	0.45	0.65	0.25	0.75			

1.7 **FUNCTIONAL DIAGRAM**





1.8 <u>MATERIALS AND FINISHES</u>

1.8.1CaseThe resistive element deposited on the alumina substrate shall be covered with a suitable coating.

1.8.2 <u>Terminations</u> The components shall be terminated with tin-lead plating (minimum 6% lead) with nickel underplating.

2. <u>REQUIREMENTS</u>

2.1 <u>GENERAL</u>

The complete requirements for procurement of the components specified herein are as stated in this specification and the ESCC Generic Specification. Permitted deviations from the Generic Specification, applicable to this specification only, are listed below.

Permitted deviations from the Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirement and do not affect the component's reliability, are listed in the appendices attached to this specification.

- 2.1.1 Deviations from the Generic Specification
- 2.1.1.1 Deviations from Screening Tests (Chart F3)
 - (a) Para. 8.1 Overload: Not applicable.
 - (b) Para. 8.2, Non-Linearity: Not applicable.
 - (c) Para. 8.4 Burn-in:

Burn-in shall be replaced by an Overload test in accordance with Para. 8.1 of the Generic Specification with conditions as follows.

Measurement of Resistance shall be performed before and after application of the Overload in accordance with Room Temperature Electrical Measurements in the Detail Specification, with the results noted against component jig position. No recovery period is required prior to the measurement performed after application of the Overload. Resistance Change after application of the Overload shall be calculated on a GONOGO basis with the following drift limit applied. Overload conditions:

- Ambient Temperature: +15 to +35°C
- Test Voltage:

Variant 01: $\sqrt{(3R_n)V}$
Variant 02: $\sqrt{(4R_n)V}$
Variant 03: $\sqrt{(8R_n)V}$

Duration: 1ms

Resistance Change drift limit: $\pm (0.05+0.01\Omega x 100/R_n)\%$

(d) Para. 6.4 Check for Lot Failure: Any Resistance Change failures after Overload shall be counted as limit failures.



PAGE 9 ISSUE 2 Draft B

2.1.1.2 Deviations from Qualification and Periodic Tests (Chart F4)

(a) Para. 8.9, Vibration: Not applicable.

2.2 MARKING

The marking of all components delivered to this specification shall be in accordance with the requirements of ESCC Basic Specification No. 21700. When the component is too small to accommodate all of the marking specified, as much as space permits shall be marked and the marking information, in full, shall accompany each component in its primary package.

The information to be marked and the order of precedence, shall be as follows:

- (a) The ESCC qualified components symbol (for ESCC qualified components only).
- (b) The ESCC Component Number.
- (c) Traceability information.

2.3 ROBUSTNESS OF TERMINATIONS - SUBSTRATE BENDING TEST

The test conditions for the substrate bending test, as specified in the ESCC Generic Specification, shall be as follows:

Number of Bends:	10
Deflection:	2mm
Duration:	5±1s

2.4 RESISTANCE TO SOLDERING HEAT

The test conditions for Resistance to Soldering Heat, tested as specified in the ESCC Generic Specification, shall be as follows:

Temperature:	260°C
Duration:	10(+0-1)s

2.5 ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES

2.5.1 <u>Room Temperature Electrical Measurements</u> The measurements shall be performed at T_{amb} =+22 ±3°C.



ISSUE 2 Draft B

Characteristics	Symbols	ESCC 4001 Test	Tolerance	Limits		Units
		Method and Conditions	(± %)	Min	Max	
Resistance	R _A	Para. 8.3.1.1	0.1	0.999 R _n	1.001 R _n	Ω
			0.5	0.995 R _n	1.005 R _n	
			1	0.99 R _n	1.01 R _n	
3rd Harmonic Attenuation	A ₃	IEC Publication No. 60440 Note 1	All	Note 2	-	dB
Insulation Resistance	R _I	Para. 8.3.1.2 V=100V Note 3	All	1000	-	MΩ

NOTES:

1. Measurement of 3rd Harmonic Attenuation may be performed at the same time as the electrical measurements immediately after application of Overload during Screening Tests.



2. The minimum limit shall be as follows:

3. Guaranteed but not tested during Screening Tests.



ISSUE 2 Draft B

2.5.2 <u>High and Low Temperatures Electrical Measurements</u>

Characteristics	Symbols	s ESCC 4001 Test Method and Conditions		Lin	nits	Units
				Min	Max	
Resistance Change be- tween -55 $(+3-0)^{\circ}$ C and $+22 \pm 3^{\circ}$ C	$\Delta R_A/R_A$	Para. 8.3.1.1 Note 1	$TC = \pm 15 \times 10^{-6/0}C$ $TC = \pm 25 \times 10^{-6/0}C$ $TC = \pm 50 \times 10^{-6/0}C$	-0.12 -0.2 -0.4	+0.12 +0.2 +0.4	%
Resistance Change be- tween +125 (+0 -3) $^{\circ}$ C and +22 ± 3 $^{\circ}$ C	$\Delta R_A/R_A$	Para. 8.3.1.1 Note 1	$TC = \pm 15 \times 10^{-6/0}C$ $TC = \pm 25 \times 10^{-6/0}C$ $TC = \pm 50 \times 10^{-6/0}C$	-0.159 -0.265 -0.53	+0.159 +0.265 +0.53	%

NOTES:

1. The measurements shall be performed on a sample of 5 components selected from the total production lot. The sample may be mounted as specified in the ESCC Generic Specification but then shall not form part of the delivery lot as mounting is considered to be destructive.

2.6 INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS

The components shall be mounted as specified in the ESCC Generic Specification.

Unless otherwise specified, the measurements shall be performed at T_{amb} =+22 ±3°C.

Unless otherwise specified the test methods and test conditions shall be as per the corresponding test defined in Room Temperature Electrical Measurements.

Test Reference per	Characteristics	Symbols	Limits		Units
ESCC No. 4001			Min	Max	
Rapid Change of Temperature					
Initial Measurement	Resistance	R _A	Record	Values	
Final Measurement	Change in Resistance	$\Delta R_A/R_A$	±(0.1+0.019	Ω x 100/R _n)	%
Robustness of Terminations					
Initial Measurement	Resistance	R _A	Record	Values	
Final Measurement	Change in Resistance	$\Delta R_A/R_A$	±(0.05+0.01	Ω x 100/R _n)	%
Resistance to Soldering Heat					
Initial Measurement	Resistance	R _A	Record	Values	
Final Measurement	Change in Resistance	$\Delta R_A/R_A$	±(0.02+0.01	Ω x 100/R _n)	%
Solderability					
Initial Measurement	Resistance	R _A	Record	Values	
Final Measurement	Change in Resistance	$\Delta R_A/R_A$	±(0.02+0.01	Ω x 100/R _n)	%
Climatic Sequence					



Test Reference per	Characteristics	Symbols	Limits		Units
ESCC No. 4001			Min	Max	
Initial Measurements (Procedure 1)	Resistance (after drying)	R _A	Record Values		
Final Measurements	Change in Resistance	$\Delta R_A/R_A$	±(0.1+0.02Ω x 100/R _n)		%
	Insulation Resistance	RI	1000	-	MΩ
Operating Life					
Initial Measurement (0 hour)	Resistance	R _A	Record	Values	
Intermediate Measurements (1000 hours)	Change in Resistance	$\Delta R_A/R_A$	±(0.05+0.01	Ω x 100/R _n)	%
Final Measurements	Change in Resistance	$\Delta R_A/R_A$	±(0.1+0.02Ω x 100/R _n)		%
(2000 hours)	Insulation Resistance	R _I	1000	-	MΩ

2.7 OPERATING LIFE CONDITIONS

Characteristics	Symbol	Condition	Unit
Ambient Temperature	T _{amb}	+70 ±3	°C
Test Voltage	V _T	$\sqrt{(P_n x R_n)}$ or U _L whichever is less	V