



## DOCUMENT CHANGE REQUEST

DCR number 736 Changes required for: General

Date: 2015/07/14

Date sent: 2012/06/18

Status: IMPLEMENTED

Originator: Steve Thacker

Organisation: ESCC Executive  
Secretariat

Title: Capacitors Fixed Chips Ceramic Dielectric Type II, based on type 0805

Number: 3009/008

Issue: 3

Other documents affected:

Page:

Total reformat/re-write of ESCC Detail Specification 3009/008 issue 3 as part of the ongoing conversion of legacy ESA/SCC specifications to the ESCC format as well as reflecting changes resulting from the conversion of ESCC Generic Specification No. 3009 issue 1 (per DCR695).

The layout, format and general content of 3009/008 issue 4 is based on other converted ESCC Detail Specifications (see attached for proposed 3009/008 issue 4 Draft B).

The technical content of ESCC 3009/008 issue 4 remains closely based on the original ESCC 3009/008 issue 3 except as detailed herein.

Paragraph:

see below

Original wording:

see original ESCC 3009/008 issue 3

Proposed wording:

Total reformat of this Detail Specification (from the range of various ESCC Detail Specifications, 3009/xxx, for capacitors under Generic Specification No. 3009) as part of the ongoing conversion to the ESCC format.

See below for summary of changes, also see attached the proposed 3009/008 Issue 4 Draft B.

Note: known support for active procurement against this specification includes the following Manufacturers:

- AVX-TPC/France (ESCC Qualified for Variant 01, 03, 06, 07)
- Eurofarad/France (is willing to support procurement).
- Syfer/UK (is willing to support procurement of Variant 01 & 06).

Summary of changes to the current format, layout and content is as follows:

1) General



## DOCUMENT CHANGE REQUEST

DCR number 736 Changes required for: General

Date: 2015/07/14

Date sent: 2012/06/18

Status: IMPLEMENTED

Originator: Steve Thacker

Organisation: ESCC Executive  
Secretariat

Rewording and restructure of various sections and paragraphs of the specification, plus other editorial changes based on the layout and editorial content of other Detail Specifications already converted to ESCC format.

In addition, editorial and technical amendments resulting from the changes made to the test requirements of the Generic Specification No. 3009.

Specific amendments include:

- Table 3: Delete Insulation Resistance, and Temperature Characteristic for each capacitance value [ Test No. 5(i) ] (due to SCC level B being deleted)
- Para. 4.7.1 & Table 4 is deleted (due to SCC level B being deleted)
- Table 6 only includes specified electrical measurement requirements as required for the various Chart F4 Qual level tests (editorial change)
- Table 6: Adhesion is renamed as Robustness of Terminations
- Table 6: add note that the capacitance values recorded during Mounting may be used as initial measurements for other tests (to provide the same flexibility included in 3009 issue 1)

2) Table 1(a), Para 4.4.1, Figure 2, Table 3 (Para 1.4.2 in issue 4)

All component range and selection options (including Variant, style, capacitance, tolerance, voltage, temperature characteristic, dimensions and terminal materials, weight) are brought together under a single Para. (editorial changes for clarification purposes)

3) Table 1(a), Table 1(b), Para 4.5.3.3

The range of components including Capacitance and Rated Voltage is expanded to also include the range supported by Syfer:

Note – The Syfer range is as follows:

16V: 100pF to 330nF

25V: 100pF to 220nF

50V: 100pF to 220nF

100V: 100pF to 47nF

200V: 100pf to 27nF

4) Figure 3. Functional Diagram is simplified (i.e. symbol 'C' is removed)

5) Para 3. Delete added symbols (editorial change: as they are no longer required by ESCC 21300)

6) Para 4.4.1

Solder coating definition is simplified to be the industry standard definition: Sn62.

Delete statements, "All the above Variants are suitable for reflow soldering." and "Variants 06 and 07 have the preferred termination finish for the specified chip size (see Figure 2)". (remove unnecessary and inappropriate comments; editorial



## DOCUMENT CHANGE REQUEST

DCR number 736 Changes required for: General

Date: 2015/07/14

Date sent: 2012/06/18

Originator: Steve Thacker

Organisation: ESCC Executive  
Secretariat

Status: IMPLEMENTED

change)

7) Table 2 & Table 6: Units for Insulation Resistance are rewritten as Mohm.uF (instead of 's')

8) Table 3 Temperature Characteristic Test No. 5(ii) (Para 2.3.2 in issue 4)

Clarify that the 1st test condition is 'VT = no voltage applied' (rather than 'VT = 0V')

Amend remark to read "... 5 components from each manufacturing lot ..." (instead of "5 parts for each dielectric lot") (to be consistent with ESCC terminology & the Generic spec).

Clarify that Temperature Characteristic for VT = UR, is not applicable & not measured for Variant 07.

9) Table 5 (Para 2.5 in issue 4)

Delete test conditions that are already specified in the Generic spec (Temperature & Voltage).

10) Appendix A

Delete appendix A for Vitramon/UK (who longer support ESCC procurement)

Justification:

Part of the ongoing conversion of legacy ESA/SCC specifications to the ESCC format. Amendments are made to the format and presentation to be consistent with the various other ESCC Detail Specifications, already converted to ESCC format, as well as the ESCC Generic Specification No. 3009 issue 2.

See also change details for justification for specific items above.


Attachments:

3009008\_draft\_4i\_for\_final\_review.docx, 3009008\_draft\_4b\_in\_review.pdf

Modifications:

Draft 4 i is approved

Approval signature:

A handwritten signature in black ink, appearing to read "R. S. Hart" with a stylized flourish at the end.

Date signed:

2015-07-14