



**CAPACITORS, FIXED, DC SELF-HEALING,
METALLISED FILM DIELECTRIC,**

BASED ON TYPE PM90S

ESCC Detail Specification No. 3006/020

Issue 2	September 2013
---------	----------------



LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2013. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

DOCUMENTATION CHANGE NOTICE

(Refer to <https://escies.org> for ESCC DCR content)

DCR No.	CHANGE DESCRIPTION
799	Specification upissued to incorporate editorial changes per DCR.

TABLE OF CONTENTS

1	GENERAL	6
1.1	SCOPE	6
1.2	RANGE OF COMPONENTS AND SIZE VARIANTS	6
1.3	MAXIMUM RATINGS	6
1.4	PARAMETER DERATING INFORMATION (FIGURE 1)	6
1.5	PHYSICAL DIMENSIONS	6
1.6	FUNCTIONAL DIAGRAM	6
2	APPLICABLE DOCUMENTS	6
3	TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS	6
4	REQUIREMENTS	13
4.1	GENERAL	13
4.2	DEVIATIONS FROM GENERIC SPECIFICATION	13
4.2.1	Deviations from Special In-process Controls	13
4.2.2	Deviations from Final Production Tests (Chart II)	13
4.2.3	Deviations from Burn-in and Electrical Measurements (Chart III)	13
4.2.4	Deviations from Qualification Tests (Chart IV)	13
4.2.5	Deviations from Lot Acceptance Tests (Chart V)	13
4.3	MECHANICAL REQUIREMENTS	13
4.3.1	Dimension Check	13
4.3.2	Weight	13
4.3.3	Robustness of Terminations	14
4.4	MATERIALS AND FINISHES	14
4.4.1	Case	14
4.4.2	Lead Material and Finish	14
4.5	MARKING	14
4.5.1	General	14
4.5.2	Polarity	14
4.5.3	The ESCC Component Number	14
4.5.4	Electrical Characteristics and Ratings	15
4.5.4.1	CAPACITANCE VALUES	15
4.5.4.2	TOLERANCES	15
4.5.4.3	RATED VOLTAGE	15
4.5.5	Traceability Information	15
4.6	ELECTRICAL MEASUREMENTS	16
4.6.1	Electrical Measurements at Room Temperature	16

4.6.2	Electrical Measurements at High and Low Temperatures	16
4.6.3	Circuits for Electrical Measurements (Figure 4)	16
4.7	BURN-IN TESTS	16
4.7.1	Parameter Drift Values	16
4.7.2	Conditions for Burn-in	16
4.7.3	Electrical Circuits for Burn-in (Figure 5)	16
4.8	ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESCC GENERIC SPECIFICATION NO. 3006)	18
4.8.1	Measurements and Inspections on Completion of Environmental Tests	18
4.8.2	Measurements and Inspections at Intermediate Points during Endurance Tests	18
4.8.3	Measurements and Inspections on Completion of Endurance Tests	18
4.8.4	Conditions for Operating Life Tests (Part of Endurance Testing)	18
4.8.5	Electrical Circuits for Operating Life Tests (Figure 5)	18

1 GENERAL

1.1 SCOPE

This specification details the ratings, physical and electrical characteristics, test and inspection data for Capacitors, Fixed, DC Self-Healing, Metallised Film Dielectric, based on Type PM90S. It shall be read in conjunction with ESCC Generic Specification No. 3006, the requirements of which are supplemented herein.

1.2 RANGE OF COMPONENTS AND SIZE VARIANTS

The range of capacitors and size variants covered by this specification are scheduled in Table 1(a).

1.3 MAXIMUM RATINGS

The maximum ratings, which shall not be exceeded at any time during use or storage, applicable to the capacitors specified herein, are scheduled in Table 1(b).

1.4 PARAMETER DERATING INFORMATION (FIGURE 1)

Not applicable.

1.5 PHYSICAL DIMENSIONS

The physical dimensions of the capacitors specified herein are shown in Figure 2.

1.6 FUNCTIONAL DIAGRAM

The functional diagram for the capacitors specified herein is shown in Figure 3.

2 APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. 3006 for Capacitors, Fixed, Film Dielectric.

3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 shall apply.

TABLE 1(a) - RANGE OF COMPONENTS AND SIZE VARIANTS

(1) Item No.	(2) Capacitance Value (C) (µF)	(3) DC Rated Voltage (U _R) (V)	(4) AC Rated Current (I _{RA}) (A)	(5) Size Variants (Note 2)	(6) Weight (g)
01	8.2	50	3.1	01, 09, 17	4.9
02	10	50	3.8	01, 09, 17	4.9
03	12	50	4.0	01, 09, 17	4.9
04	15	50	5.0	02, 10, 18	6
05	18	50	6.9	03, 11, 19	9.5
06	22	50	8.4	03, 11, 19	9.5
07	27	50	10.4	04, 12, 20	13.6
08	33	50	12.5	04, 12, 20	13.6
09	33	50	7.2	06, 14	21.2
10	39	50	12.5	04, 12, 20	13.6
11	39	50	8.5	06, 14	21.2
12	47	50	12.5	05, 13, 21	20.4
13	47	50	10.3	06, 14	21.2
14	56	50	12.5	05, 13, 21	20.4
15	68	50	15	07, 15	37.3
16	82	50	15	07, 15	37.3
17	100	50	15	07, 15	37.3
18	120	50	15	08, 16	54.2
19	150	50	15	08, 16	54.2
20	3.3	100	1.6	01, 09, 17	4.9
21	3.9	100	2.0	01, 09, 17	4.9
22	4.7	100	2.4	01, 09, 17	4.9
23	5.6	100	2.8	01, 09, 17	4.9
24	6.8	100	3.1	01, 09, 17	4.9
25	8.2	100	3.7	02, 10, 18	6
26	10	100	5.1	03, 11, 19	9.5
27	12	100	6.1	03, 11, 19	9.5
28	15	100	7.7	04, 12, 20	13.6
29	18	100	9.2	04, 12, 20	13.6
30	18	100	6.3	06, 14	21.2
31	22	100	10.1	04, 12, 20	13.6
32	22	100	7.7	06, 14	21.2
33	27	100	12.5	05, 13, 21	20.4
34	33	100	11.4	06, 14	21.2
35	33	100	12.5	05, 13, 21	20.4
36	39	100	13.5	07, 15	37.3
37	47	100	15	07, 15	37.3
38	56	100	15	07, 15	37.3
39	68	100	15	08, 16	54.2
40	82	100	15	08, 16	54.2
41	100	100	15	08, 16	54.2
42	1	250	1.2	01, 09, 17	4.9

(1) Item No.	(2) Capacitance Value (C) (μF)	(3) DC Rated Voltage (U _R) (V)	(4) AC Rated Current (I _{RA}) (A)	(5) Size Variants (Note 2)	(6) Weight (g)
43	1.2	250	1.3	01, 09, 17	4.9
44	1.5	250	1.5	01, 09, 17	4.9
45	1.8	250	1.8	01	4.9
46	2.2	250	2.2	01, 09, 17	4.9
47	2.7	250	2.8	01, 09, 17	4.9
48	3.3	250	3.4	02, 10, 18	6
49	3.9	250	4.0	02, 10, 18	6
50	4.7	250	4.8	03, 11, 19	9.5
51	5.6	250	5.8	03, 11, 19	9.5
52	6.8	250	7.5	04, 12, 20	13.6
53	6.8	250	4.6	06, 14	21.2
54	8.2	250	8.5	04, 12, 20	13.6
55	10	250	10.3	04, 12, 20	13.6
56	10	250	6.7	06, 14	21.2
57	12	250	12.4	05, 13, 21	20.4
58	12	250	8.0	06, 14	21.2
59	15	250	12.5	05, 13, 21	20.4
60	18	250	12	07, 15	37.3
61	22	250	15	07, 15	37.3
62	27	250	15	07, 15	37.3
63	33	250	15	08, 16	54.2
64	39	250	15	08, 16	54.2
65	0.39	400	1.1	01, 09, 17	4.9
66	0.47	400	1.3	01, 09, 17	4.9
67	0.56	400	1.3	01, 09, 17	4.9
68	0.68	400	1.6	01, 09, 17	4.9
69	0.82	400	1.9	01, 09, 17	4.9
70	1	400	2.4	02, 10, 18	6
71	1.2	400	2.9	02, 10, 18	6
72	1.5	400	3.6	03, 11, 19	9.5
73	1.8	400	4.3	03, 11, 19	9.5
74	2.2	400	5.3	04, 12, 20	13.6
75	2.2	400	3.0	06, 14	21.2
76	2.7	400	6.0	04, 12, 20	13.6
77	3.3	400	7.9	04, 12, 20	13.6
78	3.3	400	4.5	06, 14	21.2
79	3.9	400	9.4	05, 13, 21	20.4
80	4.7	400	6.4	06, 14	21.2
81	4.7	400	11.3	0.5, 13, 21	20.4
82	5.6	400	7.6	07, 15	37.3
83	6.8	400	9.3	07, 15	37.3
84	8.2	400	11.5	07, 15	37.3
85	10	400	14	07, 15	37.3

(1) Item No.	(2) Capacitance Value (C) (μF)	(3) DC Rated Voltage (U _R) (V)	(4) AC Rated Current (I _{RA}) (A)	(5) Size Variants (Note 2)	(6) Weight (g)
86	12	400	15	08, 16	54.2
87	15	400	15	08, 16	54.2
88	0.22	630	0.9	01, 09, 17	4.9
89	0.27	630	1.1	01, 09, 17	4.9
90	0.33	630	1.3	02, 10, 18	6
91	0.39	630	1.6	02, 10, 18	6
92	0.47	630	1.9	03, 11, 19	9.5
93	0.56	630	2.3	03	9.5
94	0.68	630	2.8	03, 11, 19	9.5
95	0.82	630	3.3	04, 12, 20	13.6
96	1	630	4.1	04, 12, 20	13.6
97	1	630	2.2	06, 14	21.2
98	1.2	630	5.0	04	13.6
99	1.5	630	3.3	06, 14	21.2
100	1.5	630	6.1	05, 13, 21	20.4
101	1.8	630	4.0	06, 14	21.2
102	1.8	630	7.3	05, 13, 21	20.4
103	2.2	630	4.9	07, 15	37.3
104	2.7	630	6.0	07, 15	37.3
105	3.3	630	7.3	07, 15	37.3
106	3.9	630	8.7	07, 15	37.3
107	4.7	630	10.3	08, 16	54.2
108	5.6	630	12.5	08, 16	54.2

NOTES

1. The capacitors have tolerances of ±10% and ±20% for all values.
2. For size variants, see Figure 2.

TABLE 1(b) - MAXIMUM RATINGS

No.	Characteristics	Symbol	Maximum Ratings	Unit	Remarks
1	Rated Voltage DC	U_R	See Table 1(a)	V	
2	Rated Voltage AC (50/60Hz)	U_A	35% of U_R	Vrms	
3	Rated Current AC (50/60Hz)	I_{RA}	See Table 1(a)	Arms	
4	Operating Temperature Range	T_{op}	-55 to +100	°C	T_{amb}
5	Storage Temperature Range	T_{stg}	-55 to +100	°C	
6	Soldering Temperature	T_{sol}	+260	°C	Note 1

NOTES


1. Duration 5 seconds maximum at a distance of not less than 6mm from the case and the same lead shall not be resoldered until 3 minutes have elapsed.

FIGURE 1 - PARAMETER DERATING INFORMATION

Not applicable.

FIGURE 2 - PHYSICAL DIMENSIONS

FIGURE 2(a) - VARIANTS 01 TO 08




Size Variant	A		B		B1		D		Ød		F		G		L	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
01	19.5	20.5	-	6.5	0.25	-	19.5	20.5	0.95	1.1	9.66	10.66	17.3	18.3	20	-
02	19.5	20.5	-	8	0.25	-	19.5	20.5	0.95	1.1	9.66	10.66	17.3	18.3	20	-
03	19.5	20.5	-	12.5	0.25	-	19.5	20.5	0.95	1.1	9.66	10.66	17.3	18.3	20	-
04	19.5	20.5	-	20	0.25	-	19.5	20.5	0.95	1.1	9.66	10.66	17.3	18.3	20	-
05	19.5	20.5	-	30	0.25	-	19.5	20.5	0.95	1.1	9.66	10.66	17.3	18.3	20	-
06	30.5	31.5	-	12.5	0.4	-	31.5	32.5	0.95	1.1	14.74	15.74	27.44	28.44	20	-
07	30.5	31.5	-	22	0.4	-	31.5	32.5	0.95	1.1	14.74	15.74	27.44	28.44	20	-
08	30.5	31.5	-	32	0.4	-	31.5	32.5	0.95	1.1	14.74	15.74	27.44	28.44	20	-

FIGURE 2(B) - VARIANTS 09 TO 21


VARIANTS 09 TO 16

VARIANTS 17 TO 21



Size Variant	A		B		D		d		d1		F		L	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
09	19.5	20.5	6.5	7.5	19.5	20.5	-	0.3	14.5	15.5	9.5	10.5	2.75	3.25
10	19.5	20.5	8	9	19.5	20.5	-	0.3	14.5	15.5	9.5	10.5	2.75	3.25
11	19.5	20.5	12.5	13.5	19.5	20.5	-	0.3	14.5	15.5	9.5	10.5	2.75	3.25
12	19.5	20.5	20	21	19.5	20.5	-	0.3	14.5	15.5	9.5	10.5	2.75	3.25
13	19.5	20.5	30	31	19.5	20.5	-	0.3	14.5	15.5	9.5	10.5	2.75	3.25
14	30.5	31.5	12.5	13.5	31.5	32.5	-	0.3	23.5	24.5	14.5	15.5	2.75	3.25
15	30.5	31.5	22	23	31.5	32.5	-	0.3	23.5	24.5	14.5	15.5	2.75	3.25
16	30.5	31.5	32	33	31.5	32.5	-	0.3	23.5	24.5	14.5	15.5	2.75	3.25
17	19.5	20.5	6.5	7.5	19.5	20.5	-	0.3	2	3	9.5	10.5	2.75	3.25
18	19.5	20.5	8	9	19.5	20.5	-	0.3	2	3	9.5	10.5	2.75	3.25
19	19.5	20.5	12.5	13.5	19.5	20.5	-	0.3	2	3	9.5	10.5	2.75	3.25
20	19.5	20.5	20	21	19.5	20.5	-	0.3	2	3	9.5	10.5	2.75	3.25
21	19.5	20.5	30	31	19.5	20.5	-	0.3	2	3	9.5	10.5	2.75	3.25

FIGURE 3 – FUNCTIONAL DIAGRAM



NOTES

1. These capacitors are not polarised, however, marking includes the voltage polarity symbol indicated above, which should be respected in use.

4 REQUIREMENTS

4.1 GENERAL

The complete requirements for procurement of the capacitors specified herein are stated in this specification and ESCC Generic Specification No. 3006 for Capacitors, Fixed, Film Dielectric. Deviations from the Generic Specification, applicable to this specification only, are listed in Para. 4.2.

Deviations from the applicable Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirements and do not affect the components' reliability, are listed in the appendices attached to this specification.

4.2 DEVIATIONS FROM GENERIC SPECIFICATION

4.2.1 Deviations from Special In-process Controls

None.

4.2.2 Deviations from Final Production Tests (Chart II)

(a) Para. 9.2, Seal Test: Not applicable.

4.2.3 Deviations from Burn-in and Electrical Measurements (Chart III)

(a) Para. 9.2, Seal Test: Not applicable.

4.2.4 Deviations from Qualification Tests (Chart IV)

(a) Para. 9.2, Seal Test: Not applicable.

(b) Para. 9.9, Robustness of Terminations: Shall not be performed for Variants 09 to 21.

(c) Para. 9.16, Operating Life: For Para. 9.16(c), the applied voltage shall be $1.25U_R$.

4.2.5 Deviations from Lot Acceptance Tests (Chart V)

(a) Para. 9.2, Seal Test: Not applicable.

(b) Para. 9.9, Robustness of Terminations: Shall not be performed for Variants 09 to 21.

(c) Para. 9.16, Operating Life: For Para. 9.16(c), the applied voltage shall be $1.25U_R$.

4.3 MECHANICAL REQUIREMENTS

4.3.1 Dimension Check

The dimensions of the capacitors specified herein shall be checked. They shall conform to those shown in Figure 2.

4.3.2 Weight

The maximum weight of the capacitors specified herein shall be as specified in Table 1(a).

4.3.3 Robustness of Terminations

For Variants 01 to 08, the requirements for robustness of terminations are specified in Section 9 of ESCC Generic Specification No. 3006. For the purpose of this test, the terminations are described as rigid. The test conditions shall be as follows:

Test Condition: Ua, Tensile.

Applied Force: 10 Newtons.

Duration: 5 to 10 seconds.

4.4 MATERIALS AND FINISHES

The materials and finishes shall be as specified herein. Where a definite material is not specified, a material which will enable the capacitors specified herein to meet the performance requirements of this specification shall be used. Acceptance or approval of any constituent material does not guarantee acceptance of the finished product.

4.4.1 Case

Thermo-plastic with epoxy resin filler.

4.4.2 Lead Material and Finish

The lead material shall be Type 'A' in accordance with the requirements of ESCC Basic Specification No. 23500. The finish shall be Sn95Pb5.

4.5 MARKING

4.5.1 General

The marking of all components delivered to this specification shall be in accordance with the requirements of ESCC Basic Specification No. 21700 and the following paragraphs. When the component is too small to accommodate all of the marking specified, as much as space permits shall be marked and the marking information, in full, shall accompany the component in its primary package.

The information to be marked and the order of precedence, shall be as follows:

- (a) Polarity.
- (b) The ESCC Component Number.
- (c) Electrical Characteristics and Ratings.
- (d) Traceability Information.

4.5.2 Polarity

Polarity shall be marked in accordance with Figures 2 and 3 of this specification.

4.5.3 The ESCC Component Number

The ESCC Component Number shall be constituted and marked as follows:

Example: 300602001B

- Detail Specification Number: 3006020
- Type Variant (see Table 1(a) and Figure 2): 01
- Testing Level (B or C, as applicable): B

4.5.4 Electrical Characteristics and Ratings

The electrical characteristics and ratings to be marked in the following order of precedence are:

- (a) Capacitance Value.
- (b) Tolerance.
- (c) Rated Voltage.

The information shall be constituted and marked as follows:

Example: 155KH

- Capacitance Value (1.5 μ F): 155
- Tolerance (10%): K
- Rated Voltage (250V): H

4.5.4.1 *Capacitance Values*

Capacitance values shall be coded as follows. The unit quantity for marking shall be picofarads.

Capacitance Value	Code
XX10 ³	XX3
XX10 ⁴	XX4
XX10 ⁵	XX5
XX10 ⁶	XX6
XX10 ⁷	XX7

4.5.4.2 *Tolerances*

The tolerances on capacitance values shall be indicated by the letter code specified hereafter.

Tolerance (\pm %)	Code Letter
10	K
20	M

4.5.4.3 *Rated Voltage*

The rated voltage shall be indicated by the code letters specified hereafter.

Rated Voltage (V)	Code Letter
50	C
100	E
250	H
400	K
630	Z

4.5.5 Traceability Information

Traceability information shall be marked in accordance with the requirements of ESCC Basic Specification No. 21700.

4.6 ELECTRICAL MEASUREMENTS

4.6.1 Electrical Measurements at Room Temperature

The parameters to be measured at room temperature are scheduled in Table 2. Unless otherwise specified, the measurements shall be performed at $T_{amb} = +22 \pm 3$ °C.

4.6.2 Electrical Measurements at High and Low Temperatures

The parameters to be measured at high and low temperatures are scheduled in Table 3.

4.6.3 Circuits for Electrical Measurements (Figure 4)

Not applicable.

4.7 BURN-IN TESTS

4.7.1 Parameter Drift Values

The parameter drift values applicable to burn-in are specified in Table 4 of this specification. Unless otherwise stated, measurements shall be performed at $T_{amb} = +22 \pm 3$ °C. The parameter drift values (Δ) applicable to the parameters scheduled shall not be exceeded. In addition to these drift value requirements for a given parameter, the appropriate limit value specified in Table 2 shall not be exceeded.

4.7.2 Conditions for Burn-in

The requirements for burn-in are specified in Section 7 of ESCC Generic Specification No. 3006. The conditions for burn-in shall be as specified in Table 5 of this specification. On completion of burn-in, a recovery period of 24 ± 2 hours is necessary before the end-measurements.

4.7.3 Electrical Circuits for Burn-in (Figure 5)

Not applicable.

TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE

No.	Characteristics	Symbol	ESCC 3006 Test Method	Test Condition	Limits		Unit
					Min.	Max.	
1	Capacitance	C	Para. 9.6.1.2	Test frequency: 1.0kHz	See Table 1(a) (Note 1)		μF
2	Tangent of Loss Angle	Tgδ	Para. 9.6.1.3	Test frequency: 1.0kHz	-	10	10 ⁻³
3	Insulation Resistance Terminal to Terminal	Ri	Para. 9.6.1.4	C ≤ 0.33μF: U _R ≤ 100V U _R > 100V	3750 7500	- -	MΩ
				C > 0.33μF: U _R ≤ 100V U _R > 100V	1250 2500	- -	s
4	Insulation Resistance Terminals to Case	Ri _B	Para. 9.6.1.4		50	-	GΩ
5	Voltage Proof Terminal to Terminal	VP	Para. 9.6.1.1		1.6 U _R (2)	-	V
6	Voltage Proof Terminals to Case	VP _B	Para. 9.6.1.1		2 U _R (2)	-	V

NOTES

- ± Ordered Tolerance.
- For U_R, see Column 3 of Table 1(a). For VP_B, minimum 200V.

TABLE 3 - ELECTRICAL MEASUREMENTS AT HIGH AND LOW TEMPERATURES

No.	Characteristics	Symbol	ESCC 3006 Test Method	Test Condition (Note 1)	Limits		Unit
					Min.	Max.	
1(a)	Capacitance Change	ΔC/C	Para. 9.6.1.2	T _{amb} = -55 °C Test frequency: 1.0kHz	-	-10 (2)	%
1(b)	Capacitance Change	ΔC/C	Para. 9.6.1.2	T _{amb} = +100 °C Test frequency: 1.0kHz	-	+8 (2)	%

NOTES

- These measurements shall be performed on a sample basis, Inspection Level II, AQL = 2.5%.
- Related to value recorded at T_{amb} = +22 °C.

FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS

Not applicable.

TABLE 4 - PARAMETER DRIFT VALUES

No.	Characteristics	Symbol	Spec. and/or Test Method	Test Conditions	Change Limits (Δ)	Unit
1	Capacitance Change	$\Delta C/C$	As per Table 2	As per Table 2	± 3	%

TABLE 5 - CONDITIONS FOR BURN-IN AND OPERATING LIFE TESTS

No.	Characteristic	Symbol	Condition	Unit
1	Ambient Temperature	T_{amb}	+100 (+0 -5)	$^{\circ}C$
2	Test Voltage	V_T	1.25 U_R (Note 1)	V

NOTES

1. See Column 3 of Table 1(a).

FIGURE 5 - ELECTRICAL CIRCUIT FOR BURN-IN AND OPERATING LIFE TESTS

Not applicable.

4.8 ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESCC GENERIC SPECIFICATION NO. 3006)

4.8.1 Measurements and Inspections on Completion of Environmental Tests

The parameters to be measured and inspections to be performed on completion of environmental tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

4.8.2 Measurements and Inspections at Intermediate Points during Endurance Tests

The parameters to be measured and inspections to be performed at intermediate points during endurance tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

4.8.3 Measurements and Inspections on Completion of Endurance Tests

The parameters to be measured and inspections to be performed on completion of endurance tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

4.8.4 Conditions for Operating Life Tests (Part of Endurance Testing)

The requirements for operating life testing are specified in Section 9 of ESCC Generic Specification No. 3006. The conditions for operating life testing shall be as specified in Table 5 for the burn-in test.

4.8.5 Electrical Circuits for Operating Life Tests (Figure 5)

Not applicable.

TABLE 6 - MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTING

No.	ESCC Generic Spec. No. 3006		Measurements And Inspections		Symbol	Limits		Unit
	Environmental And Endurance Tests (1)	Test Method And Conditions	Identification	Conditions		Min.	Max.	
01	Seal Test (Hermetically Sealed)	Para. 9.2	Not applicable					
02	Rapid Change of Temperature	Para. 9.3.2	Initial Measurements Capacitance Final Measurements Visual Examination Capacitance Change Tangent of Loss Angle	Table 2 Item 1 After recovery of 24±2 hours No damage Table 2 Item 1 Table 2 Item 2	C $\Delta C/C$ Tg δ	Record values -3 -	 +3 Table 2	%
03	Corrosion (Hermetically Sealed)	Para. 9.8, Half without sleeving (2)	Not applicable					
04	Robustness of Terminations	Para. 9.9 and Paras 4.2.4, 4.2.5 and 4.3.3 of this spec.	Final Measurements Visual Examination	No damage	-	-	-	
05	Resistance to Soldering Heat	Para. 9.10	Initial Measurements Capacitance Final Measurements Insulation Resistance Capacitance Change Tangent of Loss Angle	Table 2 Item 1 After recovery of 1 to 2 hrs Table 2 Item 3 Table 2 Item 1 Table 2 Item 2	C Ri $\Delta C/C$ Tg δ	Record values Table 2 -3 -	 - +3 Table 2	%
06	Solderability	Para. 9.11 Method 1	Final Measurements Visual Examination	IEC No. 68-2-20 Para. 4.6.4, 4.7.4 or 4.9.3	-	-	-	
07	Vibration	Para. 9.12	Measurements during Tests During Last Cycle Final Measurements Visual Examination	50% U _R (3) applied No intermittent contacts > 0.5ms or Open or Short Circuits No evidence of damage	- -	- -	- -	
08	Shock or Bump	Para. 9.13	Measurements during Tests During Last Cycle Final Measurements Visual Examination	50% U _R (3) applied No intermittent contacts > 0.5ms or Open or Short Circuits No evidence of damage, breakdown, arcing or fractures	- -	- -	- -	

2. If applicable.
3. For U_R , see Column 3 of Table 1(a). For VP_B , minimum 200V.
4. Greater than 50% of the value given in Table 2.
5. Less than 50% of the value given in Table 2.