



**CAPACITORS, LEADLESS SURFACE MOUNTED,
TANTALUM, SOLID ELECTROLYTE,
ENCLOSED ANODE CONNECTION**

BASED ON TYPE TAJ

ESCC Detail Specification No. 3012/001

Issue 9	April 2022
---------	------------



LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2022. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

DOCUMENTATION CHANGE NOTICE

(Refer to <https://escies.org> for ESCC DCR content)

DCR No.	CHANGE DESCRIPTION
1487	Specification upissued to incorporate changes per DCR.

TABLE OF CONTENTS

1	GENERAL	5
1.1	SCOPE	5
1.2	APPLICABLE DOCUMENTS	5
1.3	TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS	5
1.4	THE ESCC COMPONENT NUMBER AND COMPONENT TYPE VARIANTS	5
1.4.1	The ESCC Component Number	5
1.4.2	Component Type Variants and Range of Components	6
1.5	MAXIMUM RATINGS	8
1.6	PHYSICAL DIMENSIONS AND TERMINAL IDENTIFICATION	9
1.7	FUNCTIONAL DIAGRAM	9
2	REQUIREMENTS	10
2.1	GENERAL	10
2.1.1	Deviations from the Generic Specification	10
2.2	MARKING	10
2.3	ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES	10
2.3.1	Room Temperature Electrical Measurements	10
2.3.2	High and Low Temperatures Electrical Measurements	11
2.4	INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS	12
	APPENDIX A	14

1 GENERAL

1.1 SCOPE

This specification details the ratings, physical and electrical characteristics, and test and inspection data for the component type variants and/or the Component Type Variants and Range of Components specified below. It supplements the requirements of, and shall be read in conjunction with, the ESCC Generic Specification listed under Applicable Documents.

1.2 APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. [3012](#).

1.3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. [21300](#) shall apply.

1.4 THE ESCC COMPONENT NUMBER AND COMPONENT TYPE VARIANTS

1.4.1 The ESCC Component Number

The ESCC Component Number shall be constituted as follows:

Example: 301200101155MA

- Detail Specification Reference: 3012001
- Component Type Variant Number: 01 (as required)
- Characteristic code: Rated Capacitance (1.5µF): 155 (as required)
- Characteristic code: Capacitance Tolerance (±20%): M (as required)
- Rating code: DC Rated Voltage (10V): A (as required)

1.4.1.1 Characteristics and Ratings Codes

Characteristics and ratings to be codified as part of the ESCC Component Number shall be as follows:

- (a) Rated Capacitance, C_n , expressed by means of the following codes in accordance with ESCC Basic Specification No. [21700](#). The unit quantity shall be picofarad (pF).

Capacitance Value C (pF)	Code
XX 10 ⁴	XX4
XX 10 ⁵	XX5
XX 10 ⁶	XX6
XX 10 ⁷	XX7

- (b) Capacitance Tolerance expressed by the following codes in accordance with ESCC Basic Specification No. [21700](#):

Tolerance (± %)	Code
10	K
20	M

(c) DC Rated Voltage, U_R , expressed by the following codes:

DC Rated Voltage U_R (V)	Code
4	G
6.3	J
10	A
16	C
20	D
25	E
35	V
50	T

1.4.2 Component Type Variants and Range of Components

The Component Type Variants and Range of Components applicable to this specification are as follows:

Variant Number	Case Code (Style) (Note 1)	Terminal Material and Finish (Note 2)	Capacitance Range C_n (μ F) (Notes 3, 4)	DC Rated Voltage U_R (V) (Note 3)	Weight Max (g)
01	A (1206)	G16	0.1 to 10	4 to 50	0.1
02	B (1210)	G16	0.15 to 22	4 to 50	0.2
13	C (2312)	P17	0.47 to 68	4 to 50	0.3
14	D (2917)	P17	1.5 to 150	4 to 50	0.5
17	E (2917)	P17	10 to 220	4 to 50	0.7

NOTES:

1. See Para. 1.6.
2. Terminal material and finish shall in accordance with the requirements of ESCC Basic Specification No. [23500](#).

3. The following Rated Capacitance (C_n) and DC Rated Voltage (U_R) are available in the following cases (letters indicate the case code):

Capacitance C_n (μF)	DC Rated Voltage U_R							
	4V	6.3V	10V	16V	20V	25V	35V	50V
0.1							A	A
0.15							A	B
0.22							A	B
0.33							A	B
0.47						A	A, B	C
0.68					A	A	A, B	C
1				A	A	A	B	C
1.5			A	A	A	B	B, C	D
2.2		A	A	A, B	B	B	B, C	D
3.3	A	A	A	A, B	B	B, C	C	D
4.7	A	A	A, B	B	B, C	C	C, D	D
6.8	A	A, B	B	B, C	C	C, D	D	D
10	A, B	B	B, C	C	C	C, D	D	E
15	B	B, C	C	C	C, D	D	D	
22	B, C	C	C	C, D	D	D	E	
33	C	C	C, D	D	D	E		
47	C, D	C, D	C, D	D	E			
68	C, D	D	D	D	E			
100	D	D	D	E				
150	D	D	E					
220	E	E	E					

4. The following Capacitance Tolerances are available:

- $\pm 10\%$ (K)
- $\pm 20\%$ (M)

1.5 MAXIMUM RATINGS

The maximum ratings shall not be exceeded at any time during use or storage.


Maximum ratings shall only be exceeded during testing to the extent specified in this specification and when stipulated in Test Methods and Procedures of the ESCC Generic Specification.

Characteristics	Symbols	Maximum Ratings	Units	Remarks
DC Rated Voltage	U_R	See Para. 1.4.2	V	Note 1
DC Surge Voltage	U_S	$1.3 \times U_R$	V	$T_{amb} \leq +85^\circ\text{C}$
DC Category Voltage	U_C	$0.66 \times U_R$	V	
Operating Temperature Range	T_{op}	-55 to +125	$^\circ\text{C}$	T_{amb}
Rated Temperature	T_R	+85	$^\circ\text{C}$	
Upper Category Temperature	T_C	+125	$^\circ\text{C}$	
Storage Temperature Range	T_{stg}	-55 to +125	$^\circ\text{C}$	
Soldering Temperature	T_{sol}	+260	$^\circ\text{C}$	Note 2

NOTES:

1. At $T_{amb} \leq +85^\circ\text{C}$. For $T_{amb} > +85^\circ\text{C}$, derate linearly to U_C at $T_{amb} = +125^\circ\text{C}$.
2. Duration 5 seconds maximum for wave soldering and 10 seconds maximum for reflow soldering. The solderable area is the terminal pad and up to 1/3 the height of the L-shape terminal (see Para. 1.6).

1.6 PHYSICAL DIMENSIONS AND TERMINAL IDENTIFICATION




Variant Number	Case Code	Dimensions (mm)													
		L		H		H1		W		W1		A		S	
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
01	A	3	3.4	-	1.8	0.7	-	1.5	1.8	1	1.4	0.6	1.1	1.1	-
02	B	3.3	3.7	-	2.1	0.7	-	2.7	3	2	2.4	0.6	1.1	1.4	-
13	C	5.8	6.2	-	2.8	0.7	-	3.1	3.4	2	2.4	1.1	1.6	2.9	-
14	D	7.1	7.5	-	3.1	0.7	-	4.2	4.5	2.2	2.6	1.1	1.6	4.4	-
17	E	7.1	7.5	-	4.3	0.7	-	4.2	4.5	2.2	2.6	1.1	1.6	4.4	-

NOTES:

- Terminal identification: The anode terminal shall be indicated by a polarity stripe marked on the top surface of the component. For qualified components, the ESCC qualified components symbol may be used to indicate the anode terminal.

1.7 FUNCTIONAL DIAGRAM



Terminal 1: Anode

Terminal 2: Cathode

2 REQUIREMENTS

2.1 GENERAL

The complete requirements for procurement of the components specified herein are as stated in this specification and the ESCC Generic Specification. Permitted deviations from the Generic Specification, applicable to this specification only, are listed below.

Permitted deviations from the Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirement and do not affect the component's reliability, are listed in the appendices attached to this specification.

2.1.1 Deviations from the Generic Specification

None.

2.2 MARKING

The marking shall be in accordance with the requirements of ESCC Basic Specification No. 21700. The information to be marked shall be:

- (a) Terminal Identification (see Para. 1.6).
- (b) The ESCC qualified components symbol (for ESCC qualified components only).
- (c) The ESCC Component Number (see Para. 1.4.1).
- (d) Traceability information.

2.3 ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES

Electrical measurements shall be performed at room, high and low temperatures.

2.3.1 Room Temperature Electrical Measurements

The measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

Characteristics	Symbols	Test Method and Conditions	Tolerance	Limits		Units
				Min	Max	
Capacitance	C	ESCC No. 3012	$\pm 10\%$ $\pm 20\%$	$0.9C_n$ $0.8C_n$	$1.1C_n$ $1.2C_n$	μF
DC Leakage Current	I_L	ESCC No. 3012	All	-	$0.01C_n \times U_R$ or (1) 1	μA
Dissipation Factor	DF	ESCC No. 3012 For $U_R < 10V$: For $U_R \geq 10V, C \leq 1\mu F$: For $U_R \geq 10V, C > 1\mu F$:	All	- - -	6 4 6	%

NOTES:

- 1. Whichever is greater.

2.3.2 High and Low Temperatures Electrical Measurements

Characteristics	Symbols	Test Method and Conditions (Note 1)	Tolerance	Limits		Units
				Min	Max	
Capacitance	C	ESCC No. 3012				μF
		$T_{amb} = -55 (+3 -0)^{\circ}C:$	±10% ±20%	0.828C _n 0.736C _n	1.1C _n 1.2C _n	
		$T_{amb} = +85 \pm 3^{\circ}C:$	±10% ±20%	0.9C _n 0.8C _n	1.188C _n 1.296C _n	
		$T_{amb} = +125 (+0 -3)^{\circ}C:$	±10% ±20%	0.9C _n 0.8C _n	1.232C _n 1.344C _n	
DC Leakage Current	I _L	ESCC No. 3012	All			μA
		$T_{amb} = +85 \pm 3^{\circ}C, V = U_R \pm 2%:$	-	-	$0.1C_n \times U_R$ or (2) 1	
		$T_{amb} = +125 (+0 -3)^{\circ}C, V = U_C \pm 2%:$	-	-	$0.125C_n \times U_R$ or (2) 1	
Dissipation Factor	DF	ESCC No. 3012	All			%
		$T_{amb} = -55 (+3 -0)^{\circ}C:$	-	-	9	
		$T_{amb} = +85 \pm 3^{\circ}C:$	-	-	7.2	
		$T_{amb} = +125 (+0 -3)^{\circ}C:$	-	-	9	

NOTES:

1. Measurements shall be performed on a sample of 5 components from each manufacturing lot and each capacitance value with 0 failures allowed. In the event of any failure a 100% inspection may be performed.
2. Whichever is greater.

2.4 INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS

Unless otherwise specified, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

Unless otherwise specified the test methods and test conditions shall be as per the corresponding test defined in Para. 2.3.1 Room Temperature Electrical Measurements.

Test Reference per ESCC No. 3012	Characteristics	Symbols	Limits		Units
			Min	Max	
Mounting Initial Measurements	Capacitance	C	Note 1		μF
	Final Measurements	Capacitance Capacitance Change DC Leakage Current Dissipation Factor	C $\Delta C/C$ I_L DF	Record Value -5 +5 - Note 1 - Note 1	μF % μA %
Robustness of Terminations Initial Measurements	Capacitance	C	Note 2		μF
	Final Measurements	Capacitance Capacitance Change	C $\Delta C/C$	Record Value -5 +5	μF % (2)
Rapid Change of Temperature Initial Measurements	Capacitance	C	Note 2		μF
	Final Measurements	Capacitance Capacitance Change DC Leakage Current Dissipation Factor	C $\Delta C/C$ I_L DF	Record Value -5 +5 - Note 1 - Note 1	μF % (2) μA %
Vibration During Last Sweep Cycle	No intermittent contact $\geq 0.5ms$, arcing, or open/short circuits	-	-	-	-
Climatic Sequence Initial Measurements	Capacitance	C	Note 2		μF
	Dry Heat	DC Leakage Current (at $+125^{\circ}C$; U_c)	I_L	- Note 3	μA
Final Measurements	Capacitance Capacitance Change DC Leakage Current Dissipation Factor	C $\Delta C/C$ I_L DF	Record Value -5 +5 - Note 1 - Note 4	μF % (2) μA %	
	High and Low Temperature Stability				
Step 1 (at $+22^{\circ}C$)	Note 1 (All Characteristics)	Note 1	Note 1		
Step 2 (at $-55^{\circ}C$)	Note 3 (All Characteristics)	Note 3	Note 3		
Step 3 (at $+22^{\circ}C$)	Note 1 (All Characteristics)	Note 1	Note 1		
Step 4 (at $+85^{\circ}C$)	Note 3 (All Characteristics)	Note 3	Note 3		
Step 5 (at $+125^{\circ}C$)	Note 3 (All Characteristics)	Note 3	Note 3		
Step 6 (at $+22^{\circ}C$)	Note 1 (All Characteristics)	Note 1	Note 1		

Test Reference per ESCC No. 3012	Characteristics	Symbols	Limits		Units
			Min	Max	
Surge Voltage Final Measurements	Capacitance	C	Note 1		μF
	DC Leakage Current	I _L	-	Note 1	μA
	Dissipation Factor	DF	-	Note 1	%
Damp Heat, Steady State Initial Measurements Final Measurements	Capacitance	C	Note 2		μF
	Capacitance	C	Record Value		μF
	Capacitance Change	ΔC/C	-5	+5	% (2)
	DC Leakage Current	I _L	-	Note 1	μA
	Dissipation Factor	DF	-	Note 4	%
Operating Life Initial Measurements Intermediate Measurements (250h and 1000h)(Note 7) Intermediate Measurements (250h)(Note 8) Final Measurements (1000h or 2000h)(Note 9)	Capacitance	C	Note 2		μF
	DC Leakage Current (at T1 = +85°C)	I _L	-	Note 5	μA
	DC Leakage Current (at T2 = +125°C)	I _L	-	Note 5	μA
	DC Leakage Current (at T1 = +85°C)	I _L	-	Note 5	μA
	Capacitance	C	Record Value		μF
	Capacitance Change	ΔC/C	-5	+5	% (2)
	DC Leakage Current	I _L	-	Note 6	μA
	Dissipation Factor	DF	-	Note 1	%

NOTES:

1. As specified in Para. 2.3.1.
2. Capacitance measured during the final measurements during Mounting may be used as the initial measurement for other tests. In this case, Capacitance Change shall be referred to this initial measurement.
3. As specified in Para. 2.3.2.
4. 1.2× the limit specified in Para. 2.3.1.
5. 1.25× the limit specified in Para. 2.3.2.
6. 1.25× the limit specified in Para. 2.3.1.
7. Applicable to Qualification Testing, and to Periodic Testing for renewal of qualification after lapse.
8. Applicable to Periodic Testing for extension of qualification.
9. 1000 hours is applicable to Periodic Testing for extension of qualification. 2000 hours is applicable to Qualification Testing, and to Periodic Testing for renewal of qualification after lapse.

APPENDIX A**AGREED DEVIATIONS FOR KYOCERA AVX COMPONENTS s.r.o. (CZ)**

Items Affected	Description of Deviations
Para. 2.1.1, Deviations from the Generic Specification: Deviations from Special In-Process Controls - Chart F2	Internal Visual Inspection: Need not be performed immediately prior to encapsulation but may be performed at various stages during production, as specified in the PID.
Para. 2.1.1, Deviations from the Generic Specification: Deviations from Screening Tests - Chart F3, Deviations from Qualification and Periodic Testing - Chart F4	External Visual Inspection: Visible base material is permitted on the edges of terminals (there may be no plating on edges).