



Page 1 of 10

**DIODES, POWER RECTIFIER, HIGH EFFICIENCY, FAST
RECOVERY**

BASED ON TYPE: BYV6-200

ESCC Detail Specification No.: 0100.0011

Issue 1	January 2011
---------	--------------





LEGAL REQUIREMENTS AND COPYRIGHT

European Space Agency. Copyright ©2011. All rights reserved.

The European Space Agency disclaims any liability or responsibility, in any personal or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is retained.



Administrative/General Notes

(Refer to specifications for ESCC 001 series)

Item No.	General Description
101	Administrative/General Notes/Specified ESCC



TABLE OF CONTENTS

1	<u>GENERAL</u>	1
1.1	Scope	1
1.2	Applicable Documents	1
1.3	Terms / Definitions, Abbreviations, Symbols and Units	1
1.4	The ESCC Component Number and Component Type Variants	1
1.4.1	The ESCC Component Number	1
1.4.2	Component Type Variants	1
1.5	Maximum Ratings	1
1.6	Handling/Precautions	1
1.7	Physical Dimensions and Terminal Identification	2
1.8	Functional Diagram	1
1.9	Materials and Finish	1
2	<u>MECHANICALS</u>	1
2.1	General	1
2.1.1	Excitations from the General Specification	1
2.1.1.1	Excitations from Qualification and Periodic Tests „Drawn“	1
2.2	Mating	1
2.3	Terminal Strength	1
2.4	Electrical Measurements at Room / High ambient Temperature	1
2.4.1	Room Temperature/Relative Humidity Measurements	1
2.4.2	High ambient Temperature Electrical Measurements	1
2.4.3	Wave to Wave/Measurement Tolerances	1
2.5	Parameter Extrapolations	1
2.6	Intermediates and End Point Electrical Measurements	1
2.7	High Temperature/High Humidity Conditions	1
2.8	Power/Reliability Conditions	1
2.9	Operating Life Conditions	1
APPENDIX A		1



5. GENERAL

5.1 SCOPE

This specification details the ratings, physical and chemical characteristics and test and inspection data for the component type, values within the range of components specified below. It supplements the requirements of associated test result in conjunction with the ESCC Generic Specification listed under applicable Sections.

5.2 APPLICABLE DOCUMENTS

The following documents form part of the specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. 0001
- (b) MIL-STD-1312, Test Methods and Procedures for Semiconductor Devices

5.3 SYMBOLS, ABBREVIATIONS, DIMENSIONS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specifications No. 010001 shall apply.

5.4 THE ESCC COMPONENT NUMBERING AND COMPONENT IDENTIFICATION

5.4.1 The ESCC Component Number

The ESCC Component Number shall be constructed as follows:

Example: 01000101

- e - Basic Specification Reference: 010001
- e - Component Type (within Number 01 (as specified))

5.4.2 Component Test Values

The component type various applications this specification are as follows:

The instrumental and finish shall be in accordance with the requirements of ESCC Basic Specification No. 01001.

Variant Number	Mount or Type	Case	Configuration	Lead Material and Finish	Weight (Max. g)
01	010001-001	010-001	Single Sided	99.5	50
02	010001-002	010-002	Single Sided	99.5	50
03	010001-003	010-003	Single Sided	99.5	50
04	010001-004	010-004	Single Sided, Lead Shunt Package	99.5	50
05	010001-005	010-005	Single Sided, Lead Shunt Package	99.5	50



5.5 Maximum Ratings

The maximum ratings shall not be exceeded at any time during use or storage.

Maximum ratings shall only be exceeded during testing to the extent specified in this specification and when stipulated in Test Methods and Procedures of the ESCC General Specification.

Characteristic	Symbol	Maximum Rating	Unit	Remarks
Forward Supply Current	I_{Fmax}	100	A	Note 1
Reverse Peak Reverse Voltage	V_{Rmax}	100	V	Note 2
Storage/Output Rectified Current	I_S	10	A	100% duty cycle Note 3
Peak Forward Current	I_{Fmax}	10	A	
Operating Temperature Range (Case Temperature)	T_C	-55 to +125	°C	Note 4
Junction Temperature	T_J	+125	°C	
Storage Temperature Range	T_{stg}	-55 to +125	°C	Note 5
Handling Temperature	T_{han}	+200	°C	Note 6
Storage Temperature, Acceleration Data	$R_{stg+acc}$	1	°C/20g	Note 6

NOTES

1. Intentional pulse of 10ms duration.
2. Pulse duration time: 100µs.
3. In $T_{Fmax} + 25°C$, device linearly heats at +10°C for voltages 0V, 50, 100, 50, 0V. At $T_{Fmax} + 25°C$, device (linearly to 100, at +10°C) for duration 100, 100. For voltages 0V, 100, 100 with forward duty cycle limit, all testing performed at $T_{Fmax} + 25°C$ shall be conducted in a 100% non atmosphere.
4. Excludes 10 seconds maximum rate distance of not less than 1 foot from the device body and the same test shall not be considered until 10 minutes have elapsed.
5. Package mounted on an infinite heat sink.

5.6 Tests and ESCC Compliance

The 10A, 10V and 1000mA packages comply with the table (B-1) and therefore must not be ground-mounted (conditioned or subjected to any mechanical operation which will produce shock). The case must not be subjected to any other operation (e.g. bending) which will produce forces.



6.2 Functional Dimensions and Technical Identification

Non-Functional Dimensions (Table 6.2.1) (mm)



Symbol	Dimension (mm)		Notes
	Min	Max	
A	1.000	1.000	
B	1.000	1.000	
C	20.00	20.00	
D	0.4	0.7	
E	1	1.00	
F	0.5	0.5	
G	10.00	10.0	
H	0.50 (typical)		
I	0.00	1.00	1)
J	0.50 (typical)		
K	0.50 (typical)		
L	0.00	10.0	
M	0.50 (typical)		1)
N	-	0.00	1)
O	-	1	1)
P	0.50 (typical)		1)

Footnote

1) Transversal identification is specified by the component geometry. See Functional Diagram for the



- 1. Terminal connections.
- 2. Options.
- 3. Radius of roundish flange corner, options.
- 4. Radius of flange corner, if present.

1.8 FUNCTIONAL SYMBOLS

Terminal 1: Cathode
Terminal 2: Not connected
Terminal 3: Anode

Option 01-01-01



Terminal 1: Cathode
Terminal 2: Anode
Terminal 3: Anode

Option 01-01-02



Notes:

- 1. Terminal 2 is not connected to any lead.

1.9 TESTING & TEST METHODS

Materials and finishes shall be as follows:

- a) Case
The case shall be hermetically sealed and have a metal body. The leads pass through ceramic apertures flanged into the frame and fitted for solder to wetting.
- b) Leads
As specified in Component Type Variants.

2. REQUIREMENTS

2.1 GENERAL

The complete requirements for procurement of the components specified herein are as stated in this specification and the ESCC General Specification. Permitted deviations from the General Specification, applicable to this specification only, are indicated as follows:

Permitted deviations from the General Specification and this Serial Specification, formerly agreed with specific Manufacturers, on the basis that the alternative requirements are equivalent to the ESCC requirement and do not affect the component's reliability, are listed in the application attached to this



specification.

2.1.1 Exemptions from the General Specification

2.1.1.1 Exemptions from Qualification and Periodic Tests – Steel Fit

(a) General Exemption is not applicable.

2.2 Marking

The marking steel fasteners conforms with the requirements of ESCC Basic Specification No. 01000 and as follows:

The information to be marked on the component shall be:

- (a) Trade ESCC qualified component, symbol for ESCC qualified components only;
- (b) Trade ESCC Component Number;
- (c) Traceability information;
- (d) Marking sign for the group of steel.

2.3 Minimum Strength

The test conditions for Tensile Strength, stated as specified in the ESCC General Specification, shall be as follows:

Test Condition A, tension, with an applied force of 60% for a duration of 10s.

2.4 MECHANICAL PROPERTIES OF BOLDS, NUTS AND WASHERS (TABLE 1)

Mechanical measurements shall be performed at room, high ambient temperatures.

Consolidated values are given after the Tables.

2.4.1 Room Temperature Mechanical Measurements

The measurements shall be performed at $T_{amb} = 20 \pm 0.5^\circ\text{C}$.

Characteristic	Symbol	Typ. Min. and Max. Method	Test Conditions (Note 1)	Units		Units
				Min.	Max.	
Nominal Diameter	d_n	min 1	Min Method $v_{\theta} = 0.0007$	-	mm	mm
Nominal Voltage 1	V_{n1}	min 1	Plate Method (1) min, Note 2 Variable on (1), (2) Variable on (1)	-	1.0 0.05	V
Nominal Voltage 2	V_{n2}	min 1	Plate Method (1) min, Note 2 Variable on (1), (2) Variable on (1)	-	1.0 1.0	V



Characteristic	Symbol	EN 12756-2011 Test Method	Test Conditions (Notes 1, 2)	Limits		Units
				Min	Max	
Maximum Voltage	V_{max}	EN1	$V_1 \leq 1000V$	min	-	V
Impedance	Z	EN1	$Z_1 \leq 100 \Omega$ to 10000	-	min	Ω^2
Manufacturing Date	T_m	EN1	Manufacturing date $T_m \leq 2010$ $T_m \geq 2010$ $T_m \leq 2010$	-	min	Year
Thermal Impedance, Junction to Case	θ_{j-c}	EN1	$\theta_{j-c} \leq 100 \text{ K/W}$ $\theta_{j-c} \leq 1000$ $\theta_{j-c} \leq 10000$ $\theta_{j-c} \leq 10000$ Note 3	(Calculate θ_{j-c} see Note 4)		K/W

2.4.2 Electrical Performance Electrical Measurements

Characteristic	Symbol	EN 12756-2011 Test Method	Test Conditions (Notes 1, 2)	Limits		Units
				Min	Max	
Reverse Current	I_r	EN1	$I_{r1} \leq 1000 \mu A$ at V_{r1} EN1 Method $V_{r1} \leq 2000V$	-	min	mA
Forward voltage 1	V_{f1}	EN1	$V_{f1} \leq 1000V$ at I_{f1} EN1 EN1 Method $I_{f1} \leq 1000A$ Variable I_{f1} , $V_{f1} \leq 1000V$ Variable I_{f1} , $V_{f1} \leq 1000V$	-	min	V
			$V_{f1} \leq 1000V$ at I_{f1} EN1 EN1 Method $I_{f1} \leq 1000A$ Variable I_{f1} , $V_{f1} \leq 1000V$ Variable I_{f1} , $V_{f1} \leq 1000V$	-	min	V
Forward voltage 2	V_{f2}	EN1	$V_{f2} \leq 1000V$ at I_{f2} EN1 EN1 Method $I_{f2} \leq 1000A$ Variable I_{f2} , $V_{f2} \leq 1000V$ Variable I_{f2} , $V_{f2} \leq 1000V$	-	min	V
			$V_{f2} \leq 1000V$ at I_{f2} EN1 EN1 Method $I_{f2} \leq 1000A$ Variable I_{f2} , $V_{f2} \leq 1000V$ Variable I_{f2} , $V_{f2} \leq 1000V$	-	min	V

2.4.3 Test and Electrical Measurement Cycle

- For Voltages (4, 2) testing shall be performed with both seals combined and 1 seal together.
- Forward (1) & (2), EN1/EN2/EN3/EN4.
- Perform test only during forward bias. For reverse (3) values (electrical measurements) go to 2.4.2.
- For tests for (2), shall be defined by the Manufacturer necessary for its compliance with EN 12756-2011 Method 10.01 electrical parameter the θ_{j-c} limits specified in Maximum Ratings.
- Heat and current measurements shall be performed on a sample of 5 components with 3 failures allowed. Alternatively a 100% inspection may be performed.

**2.6. FLEXION TEST (TABLE 1)**

Unless otherwise specified, the measurements shall be performed at $T_{amb} \pm 0.5$ °C.

The test methods and test conditions shall be as per the corresponding test defined in Euro Temperature Mechanical Measurements.

The test values (a) shall not be exceeded for each characteristic specified. The corresponding ultimate test values for each characteristic shall not be exceeded.

Characteristics	Symbol	Limits		Units	
		Min Value (a)	Max Value		
			Min		Max
Flexion Current	I_{f1}	0.1 0.075 0.125	-	0.1	µA
Flexion voltage 1 Voltage 01, 02, 03 Voltage 04, 05	V_{f1}	0.005	-	0.0 0.05	V

NOTES:

1. - Reference is the greater related to the initial value.

2.8. RESISTANCE TO PENETRATION BY STITCHES AND STAPLES

Unless otherwise specified, the measurements shall be performed at $T_{amb} \pm 0.5$ °C.

The test methods and test conditions shall be as per the corresponding test defined in Euro Temperature Mechanical Measurements. The test values for each characteristic shall not be exceeded.

Characteristics	Symbol	Limits		Units
		Min	Max	
Resistance	F_{p1}	-	0.1	µA
Flexion voltage 1 Voltage 01, 02, 03 Voltage 04, 05	V_{f1}	-	0.0 0.05	V
Resistance Voltage 01, 02, 03 Voltage 04, 05	V_{f2}	-	0.0 0.0	V

2.9. HIGH TEMPERATURE RESISTANCE MEASUREMENTS (CONDITIONS)

Characteristics	Symbol	Limits	Units
ambient Temperature	T_{amb}	0.0 (0.1, 0)	°C
flexion voltage	V_{f1}	0.1	V



Characteristic	Symbol	Limits	Units
Clear Temperature	T_{clear}	±0.02 (±0.0)	°C
Junction	J	±0.0	mm

NOTES:

- For variants 04, 05 testing shall be performed with both ends embedded and J fast together.

2.8

Point B Surface Conditions

Characteristic	Symbol	Tolerances	Units
Clear Temperature	T_{clear}	±0.02 (±0.0), Note 1	°C
Junction Temperature	T_j	±0.02 (±0.0)	°C
Average Copper Thickness Deviation	T_{cu}	± 0.0, 0.02 (1)	µm

NOTES:

- Clear temperature and average current may be adjusted within the specified ranges, to attain the specified junction temperature.
- For variants 04, 05 testing shall be performed with both ends embedded and J fast together.

2.9

Construction and Installation

The construction shall be as specified in Power Bond 1.



APPENDIX

GENERAL CONDITIONS FOR PURCHASE CONTRACTS

ITEM NUMBER	DESCRIPTION OF CONDITIONS
Condition Item Production - General - Quan 10	General EC Production Item - Item of Good Quality, dimensions equal to 1.1 inch diameter and compatible for handling with a 1/8 inch nut.
Condition Item Drawing Item - Quan 10	Condition is acceptable when operating. Agreement to Item - General Data.