



**CONNECTORS, ELECTRICAL, RECTANGULAR,
MICROMINIATURE, REMOVABLE CRIMP
CONTACTS**

BASED ON TYPE MDMA

ESCC Detail Specification No. 3401/077

Issue 5	October 2015
---------	--------------



LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2015. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly by the use and application of this ESCC publication.

This publication, without prior permission of the European Space Agency and provided it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

DOCUMENTATION CHANGE NOTICE

(Refer to <https://escies.org> for ESCC DCR content)

DCR No.	CHANGE DESCRIPTION
949	Specification upissued to incorporate editorial changes per DCR.

TABLE OF CONTENTS

1	GENERAL	6
1.1	SCOPE	6
1.2	COMPONENT TYPE VARIANTS AND RANGE OF COMPONENTS	6
1.3	MAXIMUM RATINGS	6
1.4	PARAMETER DERATING INFORMATION	6
1.5	PHYSICAL DIMENSIONS	6
1.6	CONTACT ARRANGEMENTS	6
2	APPLICABLE DOCUMENTS	6
3	TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS	6
4	REQUIREMENTS	15
4.1	GENERAL	15
4.2	DEVIATIONS FROM GENERIC SPECIFICATION	15
4.2.1	Deviations from Special In-process Controls	15
4.2.2	Deviations from Final Production Tests (Chart II)	15
4.2.3	Deviations from Burn-in and Electrical Measurements (Chart III)	15
4.2.4	Deviations from Qualification Tests (Chart IV)	15
4.2.5	Deviations from Lot Acceptance Tests (Chart V)	15
4.3	MECHANICAL REQUIREMENTS	15
4.3.1	Dimension Check	15
4.3.2	Weight	15
4.3.3	Contact Capability	15
4.3.4	Contact Retention (In insert)	15
4.3.5	Mating and Unmating Forces	16
4.3.6	Insert Retention (In shell)	16
4.3.7	Jackscrew Retention	16
4.3.8	Contact Insertion and Withdrawal Forces	16
4.3.9	Engagement and Separation Forces (Male Contacts)	16
4.3.10	Oversize Pin Exclusion	16
4.3.11	Probe Damage	16
4.3.12	Solderability	16
4.4	MATERIALS AND FINISHES	16
4.4.1	Shells	16
4.4.2	Inserts	16
4.4.3	Contacts	16
4.4.4	Contact Retaining Clip	16
4.5	MARKING	17

4.5.1	General	17
4.5.2	The ESCC Component Number	17
4.5.3	Series	17
4.5.4	Characteristics	17
4.5.4.1	FIXING OPTION	17
4.5.4.2	SHELL SIZE	17
4.5.4.3	CONTACT TYPE	18
4.5.4.4	CONTACT INFORMATION	18
4.5.4.5	TRACEABILITY INFORMATION	18
4.6	ELECTRICAL MEASUREMENTS	18
4.6.1	Electrical Measurements at Room Temperature	18
4.6.2	Electrical Measurements at High and Low Temperatures	18
4.6.3	Circuits for Electrical Measurements	18
4.7	BURN-IN AND ELECTRICAL MEASUREMENTS (TABLES 4 AND 5)	18
4.8	ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESCC GENERIC SPECIFICATION NO. 3401)	19
4.8.1	Measurements and Inspections on Completion of Environmental Tests	19
4.8.2	Measurements and Inspections at Intermediate Points during Endurance Tests	19
4.8.3	Measurements and Inspections on Completion of Endurance Tests	19
4.8.4	Conditions for Operating Life Test (Part of Endurance Testing)	19
4.8.5	Electrical Circuit for Operating Life Test	19
4.8.6	Conditions for High Temperature Storage Test (Part of Endurance Testing)	19
APPENDIX A		23

1 GENERAL

1.1 SCOPE

This specification details the ratings, physical and electrical characteristics, test and inspection data for Electrical, Rectangular, Microminiature Connectors with Removable Crimp Contacts, based on type MDMA. It shall be read in conjunction with:

- ESCC Generic Specification No. 3401, Connectors, Electrical, Rectangular and Circular.
- ESCC Detail Specification No. 3401/032, Accessories for Connectors, Microminiature, 3401/029, 3401/077 and Connector Savers 3401/041.
- ESCC Detail Specification No. 3401/078, Contacts, Electrical, Crimp, for 3401/077 Microminiature Connectors based on type MDMA.
- ESCC Detail Specification No. 3401/087, Lightweight Accessories for Rectangular, Microminiature Connectors, 3401/029 and 3401/077.

the requirements of which are supplemented herein.

1.2 COMPONENT TYPE VARIANTS AND RANGE OF COMPONENTS

The different sizes of the basic type connectors specified herein, together with their mechanical characteristics, are scheduled in Table 1(a).

1.3 MAXIMUM RATINGS

The maximum ratings, which shall not be exceeded at any time during use or storage, applicable to the connectors specified herein, are given in Table 1(b).

1.4 PARAMETER DERATING INFORMATION

The derating information applicable to the connectors specified herein is shown in Figure 1.

1.5 PHYSICAL DIMENSIONS

The physical characteristics of the connectors specified herein are shown in Figure 2.

1.6 CONTACT ARRANGEMENTS

Contact arrangements are shown in Figure 3.

2 APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. 3401, Connectors, Electrical, Circular and Rectangular.
- (b) ESCC Detail Specification No. 3401/032, Accessories for Connectors, Microminiature, 3401/029, 3401/077 and Connector Savers 3401/041.
- (c) ESCC Detail Specification No. 3401/078, Contacts, Electrical, Crimp for 3401/077 Microminiature Connectors based on type MDMA.
- (d) ESCC Detail Specification No. 3401/087, Lightweight Accessories for Rectangular, Microminiature Connectors, 3401/029 and 3401/077.
- (e) MIL-DTL-45204, Gold Plating, Electro-deposited.
- (f) MIL-C-14550, Copper Plating, Electro-deposited.

3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 shall apply.

TABLE 1(a) – COMPONENT TYPE VARIANTS AND RANGE OF COMPONENTS

Variants		Shell Size Note 1	Weight Max. g Note 2	Mating Force N Max.	Unmating Force	
Shell Finish					N Max.	N Min.
Nickel	Gold					
01	02	9	2.2	20	20	1.3
01	02	15	3	33	33	2
01	02	21	3.8	47	47	2.9
01	02	25	4.3	55	55	3.5
01	02	31	5.1	69	69	4.3
01	02	37	5.9	82	82	5.1

NOTES:

1. See Figures 2.1(a) and 2.1(b).
2. Weight without cables, floating eyelets, captive nut and contacts (see Para. 4.5.4.4). Add 0.4 grammes for connectors with floating mounts and 1 gramme for connectors with captive nuts. See Figures 2.3 and 2.4 for the weight of cable and ESCC Detail Specification No. 3401/078 for contact weights.

TABLE 1(b) - MAXIMUM RATINGS

No.	Characteristic	Symbol	Maximum Rating	Unit	Remarks
1	Working Voltage	U_R	150	Vrms	Note 1
2	Rated Current with AWG24 wire AWG26 and uninsulated solid wire AWG28 wire	I_R	3.5 2.5 1.5	A	Note 2
3	Operating Temperature Range	T_{op}	-55 to +125	°C	T_{amb}
4	Storage Temperature Range	T_{stg}	-65 to +125	°C	-

NOTES:

1. At Sea Level, between contacts, and contact and shell. U_R requires derating at altitudes above sea level. See Figure 1(a).
2. I_R requires derating if the number of carrying contacts in the connector is 2 or greater. See Figure 1(b).

FIGURE 1 - PARAMETER DERATING INFORMATION

FIGURE 1(a) - WORKING VOLTAGE VERSUS ALTITUDE





FIGURE 1(b) - MAXIMUM CURRENT VERSUS NUMBER OF CONTACTS

Number of Current-Carrying Contacts per Connector	Maximum Current per Contact (A)		
	Wire Size		
	AWG24	AWG26 and Uninsulated Solid Wire	AWG28
2 - 4	2.6	2	1.4
5 - 14	2.4	1.8	1.2
15 and over	1.9	1.4	0.9

FIGURE 2 - PHYSICAL DIMENSIONS

Figure 2.1(a) – Connector Shells - Plug (Male Contacts)




Shell Size	A Max.	B Max.	C Max.	D Max.	E Max.	E		G Max.	H Max.	J Max.	M Max.	N		$\varnothing S$	
						Min.	Max.					Min.	Max.	Min.	Max.
9	19.94	8.46	10.16	6.86	7.82	14.22	14.48	4.69	10.57	4.72	7.26	2.23	2.49	2.23	2.39
15	23.75	12.27	13.97	6.86	7.82	18.03	18.29	4.69	10.57	4.72	7.26	2.23	2.49	2.23	2.39
21	27.56	16.08	17.78	6.86	7.82	21.84	22.1	4.69	10.57	4.72	7.26	2.23	2.49	2.23	2.39
25	30.1	18.62	20.32	6.86	7.82	24.38	24.64	4.69	10.57	4.72	7.26	2.23	2.49	2.23	2.39
31	33.91	22.43	24.13	6.86	7.82	28.19	28.45	4.69	10.57	4.72	7.26	2.23	2.49	2.23	2.39
37	37.72	26.24	27.94	6.86	7.82	32	32.26	4.69	10.57	4.72	7.26	2.23	2.49	2.23	2.39

NOTES:

1. All dimensions are in millimetres.

Figure 2.1(b) – Connector Shells - Receptacle (Female Contacts)



Shell Size	A	B	C	D	E	F		G	H	J	M	N		$\varnothing S$	
	Max.	Max.	Max.	Max.	Max.	Min.	Max.	Max.	Max.	Max.	Max.	Min.	Max.	Min.	Max.
9	19.94	10.16	10.16	6.86	7.82	14.22	14.48	6.38	10.9	5.05	7.59	2.23	2.49	2.23	2.39
15	23.75	13.97	13.97	6.86	7.82	18.03	18.29	6.38	10.9	5.05	7.59	2.23	2.49	2.23	2.39
21	27.56	17.78	17.78	6.86	7.82	21.84	22.1	6.38	10.9	5.05	7.59	2.23	2.49	2.23	2.39
25	30.1	20.32	20.32	6.86	7.82	24.38	24.64	6.38	10.9	5.05	7.59	2.23	2.49	2.23	2.39
31	33.91	24.13	24.13	6.86	7.82	28.19	28.45	6.38	10.9	5.05	7.59	2.23	2.49	2.23	2.39
37	37.72	27.94	27.94	6.86	7.82	32	32.26	6.38	10.9	5.05	7.59	2.23	2.49	2.23	2.39

NOTES:

1. All dimensions are in millimetres.

FIGURE 2.2 – CONTACT POSITIONS

Figure 2.2.1 – Mounting Condition




Figure 2.2.2 – Plug Male Contact





Figure 2.2.3 – Receptacle Female Contact




F		S		Z
Min.	Max.	Min.	Max.	Max.
0.25	0.91	3.3	3.66	5.49

NOTES:

1. All dimensions in millimeters.

FIGURE 2.3 – UNINSULATED SOLID WIRES ACCEPTED




Wire Size AWG	25
Max Diameter D mm	0.46
Min Diameter D mm	0.45
Min Gold Plating Thickness μm	0.5
Max. Weight g/m	1.6

FIGURE 2.4 – INSULATED SOLID WIRES ACCEPTED

		ESCC 3901/002			ESCC 3901/013		
		Wire Size AWG					
		24	26	28	24	26	28
Conductor Characteristics	Maximum Diameter mm	0.64	0.53	0.43	0.62	0.5	0.42
	Nominal Cross-section mm ²	0.21	0.15	0.1	0.22	0.14	0.1
Wire Characteristics	Maximum Diameter mm	0.88	0.78	0.68	1.04	0.89	0.82
	Maximum Weight g/m	2.64	1.93	1.23	3.34	2.3	1.8

FIGURE 2.5 – FLOATING MOUNT (Notes 2 and 3)




d	d1	ØM Max.	ØN Min.	P Max.
1	0.8	4	2.26	4.7

NOTES:

1. All dimensions are in millimetres.
2. Total Lateral Float 0.4 (typical).
3. Total Axial Float 0.4 (typical).

FIGURE 2.6 - CAPTIVE NUT




Øg	J Max.	ØM Max.
Note 2	2.6	5.1

NOTES:

1. All dimensions are in millimetres.
2. Øg: 2-56 UNC 28, Maximum Torque 0.44Nm.

FIGURE 3 – CONTACT ARRANGEMENTS


FRONT VIEW OF MALE INSERT – USE MIRROR VIEW FOR FEMALE INSERT



NOTES:

1. Only the outside contact cavities on each row are identified in the drawing, the remainder follow sequentially. Contact numbers are shown outside the insert for readability.

Contact Centres



NOTES:

1. a = Distance between contact centres: 1.27mm (typical).
2. b = Distance between rows: 1.09mm (typical).

4 REQUIREMENTS

4.1 GENERAL

The complete requirements for procurement of the connectors specified herein are stated in this specification and ESCC Generic Specification No. 3401. Deviations from the Generic Specification, applicable to this specification only, are listed in Para. 4.2.

Deviations from the applicable Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirements and do not affect the components' reliability, are listed in the appendices attached to this specification.

4.2 DEVIATIONS FROM GENERIC SPECIFICATION

4.2.1 Deviations from Special In-process Controls

None.

4.2.2 Deviations from Final Production Tests (Chart II)

(a) Para. 9.5, Magnetism Level: Not applicable.

4.2.3 Deviations from Burn-in and Electrical Measurements (Chart III)

Chart III is not applicable.

4.2.4 Deviations from Qualification Tests (Chart IV)

- (a) Para. 9.9, Seal Test: Not applicable.
- (b) Para. 9.29, Oversize Pin Exclusion: Not applicable.
- (c) Para. 9.30, Probe Damage: Not applicable.
- (d) Para. 9.31, Solderability: Not applicable.

4.2.5 Deviations from Lot Acceptance Tests (Chart V)

- (a) Para. 9.9, Seal Test: Not applicable.
- (b) Para. 9.29, Oversize Pin Exclusion: Not applicable.
- (c) Para. 9.30, Probe Damage: Not applicable.

4.3 MECHANICAL REQUIREMENTS

4.3.1 Dimension Check

The dimensions of the connectors specified herein shall be verified in accordance with the requirements set out in Para. 9.6 of ESCC Generic Specification No. 3401 and shall conform to those shown in Figure 2 of this specification. Only the underlined dimensions shall be checked during procurement.

4.3.2 Weight

The maximum weight of the connectors specified herein, without contacts and interfacial seals, shall be in accordance with the values given in Table 1(a) of this specification.

4.3.3 Contact Capability

As specified in ESCC Detail Specification No. 3401/078.

4.3.4 Contact Retention (In insert)

As specified in ESCC Detail Specification No. 3401/078.

4.3.5 Mating and Unmating Forces

The forces applied for the mating and unmating of the connectors shall conform to the values specified in Table 1(a).

4.3.6 Insert Retention (In shell)

Connector inserts shall withstand a pressure of 34.4N/cm^2 applied from the mating side to the rear side.

4.3.7 Jackscrew Retention

Not applicable.

4.3.8 Contact Insertion and Withdrawal Forces

As specified in ESCC Detail Specification No. 3401/078.

4.3.9 Engagement and Separation Forces (Male Contacts)

As specified in ESCC Detail Specification No. 3401/078.

4.3.10 Oversize Pin Exclusion

Not applicable.

4.3.11 Probe Damage

Not applicable.

4.3.12 Solderability

Not applicable.

4.4 MATERIALS AND FINISHES

The materials and finishes shall be as specified herein. Where a definite material is not specified, a material which will enable the components specified herein to meet the performance requirements of this specification shall be used. Acceptance or approval of any constituent material does not guarantee acceptance of the finished product.

4.4.1 Shells

Shells shall be made of aluminium alloy. Variant 01 shall have a minimum plating thickness of $25.4\mu\text{m}$ of electroless nickel. The plating for Variant 02 shall be $0.7\mu\text{m}$ minimum of gold with $25.4\mu\text{m}$ minimum electroless nickel underplating.

4.4.2 Inserts

Inserts shall be made of a suitable thermoplastic material.

4.4.3 Contacts

As specified in ESCC Detail Specification No. 3401/078.

4.4.4 Contact Retaining Clip

The retaining clip shall be made of beryllium copper.

4.5 MARKING

4.5.1 General

The marking of components delivered to this specification shall be in accordance with the requirements of ESCC Basic Specification No. 21700 and the following paragraphs.

Each component shall be marked in respect of:

- (a) The ESCC qualified components symbol (for ESCC qualified components only).
- (b) The ESCC Component Number.
- (c) Series.
- (d) Characteristics.
- (e) Traceability Information.

4.5.2 The ESCC Component Number

Each component shall bear the ESCC Component Number which shall be constituted and marked as follows:

Example: 340107701B

- Detail Specification Number: 3401077
- Type Variant (See Table 1(a)): 01
- Testing Level: B

4.5.3 Series

The series of the connector, MDMA, shall be marked on the connector if space permits.

4.5.4 Characteristics

The characteristics to be marked in the following order of precedence are:

- (a) Mounting.
- (b) Shell Size.
- (c) Contact Type.
- (d) Contact Information.

The information shall be constituted and marked as follows (example): Y37P-FO

- Mounting: Y
- Shell size: 37
- Contact Type: P
- Contact Information: -FO

4.5.4.1 *Fixing Option*

The letter "Y" shall indicate a floating mount. The letter "E" shall indicate captive nuts. If the shell has standard mounting holes, the letter shall be omitted.

4.5.4.2 *Shell Size*

Shell size shall be designated by the number of contacts.

Specified numbers are: 9, 15, 21, 25, 31 and 37.

4.5.4.3 *Contact Type*

Contact types shall be indicated by the following code letters.

Code Letter	Contact Type
P	Male
S	Female

4.5.4.4 *Contact Information*

-FO = Connector ordered without contacts. This information shall not be marked on the connector; it is only included on the packaging and all relevant data documentation.

Contacts must be from the same Manufacturer as the connector in which they are fitted and this shall be verified prior to assembly.

4.5.4.5 *Traceability Information*

Traceability information shall be marked in accordance with the requirements of ESCC Basic Specification No. 21700.

4.6 ELECTRICAL MEASUREMENTS

4.6.1 Electrical Measurements at Room Temperature

The parameters to be measured in respect of electrical characteristics are scheduled in Table 2. Unless otherwise specified, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

4.6.2 Electrical Measurements at High and Low Temperatures

Not applicable.

4.6.3 Circuits for Electrical Measurements

Not applicable.

4.7 BURN-IN AND ELECTRICAL MEASUREMENTS (TABLES 4 AND 5)

Not applicable.

TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE

No.	Characteristic	Symbol	ESCC 3401 Test Method	Test Condition	Limits		Unit
					Min.	Max.	
1	Insulation Resistance	R_i	Para. 9.1.1.1	Para. 9.1.1.1	5000	-	$M\Omega$
2	Voltage Proof Leakage Current	I_L	Para. 9.1.1.2	600 Vrms	-	2	mA
3	Mated Shell Conductivity (Voltage Drop) Note 1	V_D	Para. 9.1.1.4	Para. 9.1.1.4	Not applicable		mV

NOTES

1. Applicable to mated connectors with grounding option.

TABLES 3, 4 AND 5

Not applicable.

- 4.8 ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESCC GENERIC SPECIFICATION No. 3401)
- 4.8.1 Measurements and Inspections on Completion of Environmental Tests
The parameters to be measured and inspections to be performed on completion of environmental testing shall be those specified in Table 6. Unless otherwise specified, these measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}\text{C}$.
- 4.8.2 Measurements and Inspections at Intermediate Points during Endurance Tests
Not applicable.
- 4.8.3 Measurements and Inspections on Completion of Endurance Tests
The parameters to be measured and inspections to be performed on completion of endurance testing shall be those specified in Table 6. Unless otherwise specified, these measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}\text{C}$.
- 4.8.4 Conditions for Operating Life Test (Part of Endurance Testing)
Not applicable.
- 4.8.5 Electrical Circuit for Operating Life Test
Not applicable.
- 4.8.6 Conditions for High Temperature Storage Test (Part of Endurance Testing)
The requirements for the high temperature storage test are specified in Section 9 of ESCC Generic Specification No. 3401. The temperature to be applied shall be the maximum storage temperature specified in Table 1(b) of this specification.

TABLE 6 – MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL AND ENDURANCE TESTING

No.	ESCC Generic Spec. No. 3401		Measurements and Inspections		Symbol	Limits		Unit		
	Environmental and Endurance Tests Note 1	Test Method and Conditions	Identification	Conditions		Min.	Max.			
01	Seal Test	Para. 9.9	Not applicable							
02	Wiring	Para. 9.10	ESCC 3401/078		-	-	-			
03	Vibration	Para. 9.11	Initial Measurements		Tqe	Record Values				
			Coupling Screw(s) Unlocking Torque							
			Final Measurements		$\Delta Tqe/Tqe$	-25	+25		%	
			Full Engagement Coupling Screw(s) Unlocking Torque Drift							
Visual Examination		-	-	-	-					
04	Shock or Bump	Para. 9.12	Full Engagement Visual Examination		-	-	-			
05	Climatic Sequence	Para. 9.13	Dry Heat		R _i	10	-	MΩ		
			Insulation Resistance						At High Temperature Table 2, Item 1	
			Low Air Pressure		I _L	Figure 1		ESCC 3401 Para. 9.13.5		mA
			Voltage Proof Leakage Current							
			Damp Heat		R _i	Immediately after test Table 2, Item 1 After 1-24 hrs Recovery		100	-	MΩ
			Insulation Resistance							
Final Measurements		R _i	ESCC 3401 Para. 9.7		ESCC 3401 Para. 9.7		MΩ			
External Visual Inspection										
Insulation Resistance		I _L	Table 2, Item 1		Table 2, Item 1		mA			
Voltage Proof Leakage Current		Table 2, Item 2		Table 2, Item 2						
06	Plating Thickness	Para. 9.14	Thickness		-	-	-			
07	Joint Strength	Para. 9.15	ESCC 3401/078		-	-	-			
08	Rapid Change of Temperature	Para. 9.16	Visual Examination		-	-	-			
			Insulation Resistance		R _i	Table 2, Item 1		MΩ		
			Voltage Proof Leakage Current						I _L	Table 2, Item 2
Insulation Resistance		Table 2, Item 1		Table 2, Item 1						
Voltage Proof Leakage Current		Table 2, Item 2		Table 2, Item 2						
09	Contact Retention (in Insert)	Para. 9.17 & Para. 4.3.4 of this spec.	Contact Displacement		-	ESCC 3401/078				

No.	ESCC Generic Spec. No. 3401		Measurements and Inspections		Symbol	Limits		Unit
	Environmental and Endurance Tests Note 1	Test Method and Conditions	Identification	Conditions		Min.	Max.	
10	Endurance	Para. 9.18	Initial Measurements Mating/Unmating Forces Low Level Contact Resistance Mated Shell Conductivity Final Measurements Visual Examination Mating/Unmating Forces Low Level Contact Resistance Drift Mated Shell Conductivity Insulation Resistance Voltage Proof Leakage Current	- ESCC 3401/078 Table 2, Item 3 - - ESCC 3401/078 Table 2, Item 3 Table 2, Item 1 Table 2, Item 2	F R _{cl} V _D - F ΔR _{cl} V _D R _i I _L	Para. 4.3.5 of this spec. ESCC 3401/078 Not applicable - - Para. 4.3.5 of this spec. ESCC 3401/078 Not applicable Table 2, Item 1 Table 2, Item 2	N mΩ mV N mΩ mV MΩ mA	
11	Permanence of Marking	Para. 9.19	As applicable	-	-	-		
12	Mating / Unmating Forces	Para. 9.20	Force	-	F	Para. 4.3.5 of this spec.	N	
13	High Temperature Storage	Para. 9.21	Initial Measurements Low Level Contact Resistance Mated Shell Conductivity Final Measurements Visual Examination Mating/Unmating Forces Low Level Contact Resistance Drift Rated Current Contact Resistance Mated Shell Conductivity Insulation Resistance Voltage Proof Leakage Current Contact Retention (In Insert)	ESCC 3401/078 Table 2, Item 3 - - ESCC 3401/078 ESCC 3401/078 ESCC 3401/078 Table 2, Item 3 Table 2, Item 1 Table 2, Item 2 ESCC 3401/078	R _{cl} V _D - F ΔR _{cl} R _{cr} V _D R _i I _L	ESCC 3401/078 Not applicable - - Para. 4.3.5 of this spec. ESCC 3401/078 ESCC 3401/078 Not applicable Table 2, Item 1 Table 2, Item 2 ESCC 3401/078	mΩ mV N mΩ mΩ mV MΩ mA N	
14	Corrosion	Para. 9.22	Visual Examination	-	-	- -		
15	Insert Retention (In Shell)	Para. 9.23 & Para. 4.3.6 of this spec.	Visual Examination	-	-	Para. 4.3.6 of this spec.		
16	Jackscrew Retention	Para. 9.24 & Para. 4.3.7 of this spec.	Not applicable					

No.	ESCC Generic Spec. No. 3401		Measurements and Inspections		Symbol	Limits		Unit
	Environmental and Endurance Tests Note 1	Test Method and Conditions	Identification	Conditions		Min.	Max.	
17	High Temperature Measurements	Para. 9.25	Insulation Resistance	Table 2 Item 1	R _i	10	-	MΩ
18	Overload Test	Para. 9.26	Internal Temperature	-	T	-	+100	°C
			Rated Current Contact Resistance	ESCC 3401/078	R _{cr}	ESCC 3401/078		mΩ
			Mated Shell Conductivity	Table 2 Item 3	V _D	Not applicable		mV
			Insulation Resistance	Table 2 Item 1	R _i	Table 2, Item 1		MΩ
			Voltage Proof Leakage Current	Table 2 Item 2	I _L	Table 2, Item 2		mA
19	Maintenance Ageing	Para. 9.27	Visual Examination	-	-	-	-	
			Contact Retention (In insert)	ESCC 3401/078	-	ESCC 3401/078		N
			Contact insertion and Withdrawal Forces	ESCC 3401/078		ESCC 3401/078		N
20	Engage/Separation Forces	Para. 9.28 & Para. 4.3.9 of this spec.	Force	ESCC 3401/078	F	ESCC 3401/078		N
21	Oversize Pin Exclusion	Para. 9.29 & Para. 4.3.10 of this spec.	Not applicable					
22	Probe Damage	Para. 9.30 & Para. 4.3.11 of this spec.	Not applicable					
23	Solderability	Para. 9.31 & Para. 4.3.12 of this spec.	Not applicable					

NOTES

1. The tests in this Table refer to either Chart IV or V and shall be used as applicable.

APPENDIX A
AGREED DEVIATIONS FOR C&K COMPONENTS (F)

ITEMS AFFECTED	DESCRIPTION OF DEVIATIONS
Deviations from Final Production Tests (Chart II)	Para. 9.4, Contact Capability: 100% Contact Capability Test may be omitted provided that a 100% visual inspection of the contacts is performed on each batch submitted to tests defined in the C&K PID requirements.